

Package ‘regioneR’

October 9, 2015

Type Package

Title Association analysis of genomic regions based on permutation tests

Version 1.0.3

Date 2015-03-18

Author Anna Diez-Villanueva <adiez@imppc.org>, Roberto Malinverni <rmalinverni@carrerasresearch.org> and Bernat Gel <bgel@imppc.org>

Maintainer Bernat Gel <bgel@imppc.org>

Description regioneR offers a statistical framework based on customizable permutation tests to assess the association between genomic region sets and other genomic features.

License Artistic-2.0

Depends memoise, GenomicRanges, BSgenome, rtracklayer, parallel

Imports memoise, GenomicRanges, BSgenome, rtracklayer, parallel

Suggests BiocStyle, knitr, BSgenome.Hsapiens.UCSC.hg19.masked

VignetteBuilder knitr

biocViews Genetics, ChIPSeq, DNaseSeq, Methylation, CopyNumberVariation

NeedsCompilation no

R topics documented:

characterToBSGenome	2
circularRandomizeRegions	3
commonRegions	4
createRandomRegions	5
emptyCacheRegioner	6
extendRegions	7
filterChromosomes	8
getChromosomesByOrganism	9
getGenome	9
getGenomeAndMask	10

getMask	11
joinRegions	12
listChrTypes	13
localZScore	14
maskFromBSGenome	15
meanDistance	15
meanInRegions	16
mergeRegions	17
numOverlaps	18
overlapGraphicalSummary	19
overlapPermTest	20
overlapRegions	21
permTest	22
plot.permTestResults	24
plotRegions	25
randomizeRegions	26
recomputePermTest	27
resampleRegions	28
splitRegions	29
subtractRegions	30
toDataframe	31
toGRanges	32
uniqueRegions	33

Index 34

characterToBSGenome *characterToBSGenome*

Description

Given a character string with the "name" of a genome, it returns a [BSgenome](#) object if available.

Usage

```
characterToBSGenome(...)
```

Arguments

... a genome.name parameter is needed, a character string uniquely identifying a [BSgenome](#) (e.g. "hg19", "mm10" are ok, but "hg" is not)

Value

A [BSgenome](#) object

Note

This function is memoised (cached) using the `memoise` package. To empty the cache, use `forget(characterToBSGenome)`

See Also

[getGenomeAndMask](#), [maskFromBSGenome](#)

Examples

```
g <- characterToBSGenome("hg19")
```

circularRandomizeRegions

Circular Randomize Regions

Description

Given a set of regions A and a genome, this function returns a new set of regions created by applying a random spin to each chromosome.

Usage

```
circularRandomizeRegions(A, genome="hg19", mask=NULL, max.mask.overlap=NULL, max.retries=10, verbose=FALSE)
```

Arguments

A	The set of regions to randomize. A region set in any of the accepted formats by toGRanges (GenomicRanges , data.frame , etc...)
genome	The reference genome to use. A valid genome object. Either a GenomicRanges or data.frame containing one region per whole chromosome or a character uniquely identifying a genome in BSgenome (e.g. "hg19", "mm10" but not "hg"). Internally it uses getGenomeAndMask .
mask	The set of regions specifying where a random region can not be (centromeres, repetitive regions, unmappable regions...). A region set in any of the accepted formats by toGRanges (GenomicRanges , data.frame , ...). If <code>NULL</code> it will try to derive a mask from the genome (currently only works if the genome is a character string) and if <code>NA</code> it will explicitly give an empty mask.
max.mask.overlap	numeric value
max.retries	numeric value
verbose	a boolean.
...	further arguments to be passed to or from methods.

Details

This randomization strategy is useful when the spatial relation between the regions in the RS is important and has to be conserved.

Value

It returns a [GenomicRanges](#) object with the regions resulting from the randomization process.

See Also

[randomizeRegions](#), [toDataframe](#), [toGRanges](#), [getGenome](#), [getMask](#), [getGenomeAndMask](#), [characterToBSGenome](#), [maskFromBSGenome](#), [resampleRegions](#), [createRandomRegions](#)

Examples

```
A <- data.frame("chr1", c(1, 10, 20, 30), c(12, 13, 28, 40))
mask <- data.frame("chr1", c(20000000, 100000000), c(22000000, 130000000))
genome <- data.frame(c("chr1", "chr2"), c(1, 1), c(180000000, 200000000))
circularRandomizeRegions(A)
circularRandomizeRegions(A, genome=genome, mask=mask, per.chromosome=TRUE, non.overlapping=TRUE)
```

commonRegions

Common Regions

Description

Returns the regions that are common in two region sets, its intersection.

Usage

```
commonRegions(A, B)
```

Arguments

A a region set in any of the accepted formats by [toGRanges](#) ([GenomicRanges](#), [data.frame](#), etc...)

B a region set in any of the accepted formats by [toGRanges](#) ([GenomicRanges](#), [data.frame](#), etc...)

Value

It returns a [GenomicRanges](#) object with the regions present in both region sets.

Note

All metadata (additional columns in the region set in addition to chromosome, start and end) will be ignored and not present in the returned region set.

See Also

[plotRegions](#), [toDataframe](#), [toGRanges](#), [subtractRegions](#), [splitRegions](#), [extendRegions](#), [joinRegions](#), [mergeRegions](#), [overlapRegions](#)

Examples

```
A <- data.frame("chr1", c(1, 10, 20, 30), c(12, 13, 28, 40))
B <- data.frame("chr1", 25, 35)
commons <- commonRegions(A, B)
plotRegions(list(A, B, commons), chromosome="chr1", regions.labels=c("A", "B", "common"), regions.colors=3:1)
```

createRandomRegions *Create Random Regions*

Description

Creates a set of random regions with a given mean size and standard deviation.

Usage

```
createRandomRegions(nregions=100, length.mean=250, length.sd=20, genome="hg19", mask=NULL, non.overlapping=TRUE)
```

Arguments

nregions	The number of regions to be created.
length.mean	The mean size of the regions created. This is not guaranteed to be the mean of the final region set. See note.
length.sd	The standard deviation of the region size. This is not guaranteed to be the standard deviation of the final region set. See note.
genome	The reference genome to use. A valid genome object. Either a GenomicRanges or data.frame containing one region per whole chromosome or a character uniquely identifying a genome in BSgenome (e.g. "hg19", "mm10" but not "hg"). Internally it uses getGenomeAndMask .
mask	The set of regions specifying where a random region can not be (centromeres, repetitive regions, unmappable regions...). A region set in any of the accepted formats (GenomicRanges , data.frame , ...). <code>NULL</code> will try to derive a mask from the genome (currently only works if the genome is a character string) and <code>NA</code> explicitly gives an empty mask.
non.overlapping	A boolean stating whether the random regions can overlap (<code>FALSE</code>) or not (<code>TRUE</code>).

Details

A set of nregions will be created and randomly placed over the genome. The lengths of the region set will follow a normal distribution with a mean size length.mean and a standard deviation length.sd. The new regions can be made explicitly non overlapping by setting non.overlapping to TRUE. A mask can be provided so no regions fall in a forbidden part of the genome.

Value

It returns a [GenomicRanges](#) object with the regions resulting from the randomization process.

Note

If the standard deviation of the length is large with respect to the mean, negative lengths might be created. These region lengths will be transformed to into a 1 and so the, for large standard deviations the mean and sd of the lengths are not guaranteed to be the ones in the parameters.

See Also

[getGenome](#), [getMask](#), [getGenomeAndMask](#), [characterToBSGenome](#), [maskFromBSGenome](#), [randomizeRegions](#), [resampleRegions](#)

Examples

```
genome <- data.frame(c("chr1", "chr2"), c(1, 1), c(180000000, 200000000))
mask <- data.frame("chr1", c(200000000, 100000000), c(220000000, 130000000))

createRandomRegions(nregions=10, length.mean=1000, length.sd=500)

createRandomRegions(nregions=10, genome=genome, mask=mask, non.overlapping=TRUE)
```

emptyCacheRegioner *Empty Cache regioneR*

Description

Empties the caches used by the memoised function in the regioneR package.

Usage

```
emptyCacheRegioner()
```

Value

The cache is emptied

Examples

```
emptyCacheRegioner()
```

extendRegions	<i>Extend Regions</i>
---------------	-----------------------

Description

Extends the regions a number of bases at each end. Negative numbers will reduce the region instead of enlarging it.

Usage

```
extendRegions(A, extend.start=0, extend.end=0)
```

Arguments

A	a region set in any of the accepted formats by toGRanges (GenomicRanges , data.frame , etc...)
extend.start	an integer. The number of bases to be subtracted from the start of the region.
extend.end	an integer. The number of bases to be added at the end of the region.

Value

a [GenomicRanges](#) object with the extended regions.

Note

If negative values are provided and the new extremes are "flipped", the function will fail. It does not check if the extended regions fit into the genome.

See Also

[plotRegions](#), [toDataframe](#), [toGRanges](#), [subtractRegions](#), [splitRegions](#), [overlapRegions](#), [commonRegions](#), [mergeRegions](#), [joinRegions](#)

Examples

```
A <- data.frame("chr1", c(10, 20, 30), c(13, 28, 40))  
  
extend1 <- extendRegions(A, extend.start=5, extend.end=2)  
  
extend2 <- extendRegions(A, extend.start=15)  
  
extend3 <- extendRegions(A, extend.start=-1)  
  
plotRegions(list(A, extend1, extend2, extend3), chromosome="chr1", regions.labels=c("A", "extend1", "extend2", "
```

filterChromosomes	<i>filterChromosomes</i>
-------------------	--------------------------

Description

Filters the chromosomes in a region set. It can either filter using a predefined chromosome set (e.g. "autosomal chromosomes in Homo sapiens") or using a custom chromosome set (e.g. only chromosomes "chr22" and "chrX")

Usage

```
filterChromosomes(A, organism="hg", chr.type="canonical", keep.chr=NULL)
```

Arguments

A	a region set in any of the formats accepted by toGRanges (GenomicRanges , data.frame , etc...)
organism	a character indicating the organism from which to get the predefined chromosome sets. It can be the organism code as used in BSgenome (e.g. hg for human, mm for mouse...) or the full genome assembly identifier, since any digit will be removed to get the organism code.
chr.type	a character indicating the specific chromosome set to be used. Usually "autosomal" or "canonical", although other values could be available for certain organisms.
keep.chr	is a character vector stating the names of the chromosomes to keep. Any chromosome not in the vector will be filtered out. If keep.chr is supplied, organism and chr.type are ignored.

Value

A [GRanges](#) object containing only the regions in the original region set belonging to the selected chromosomes. All regions in non selected chromosomes are removed.

See Also

[getGenomeAndMask](#), [listChrTypes](#) [getChromosomesByOrganism](#)

Examples

```
g <- getGenomeAndMask("hg19")$genome
listChrTypes()
g <- filterChromosomes(g, chr.type="autosomal", organism="hg19")
g <- filterChromosomes(g, keep.chr=c("chr1", "chr2", "chr3"))
```

`getChromosomesByOrganism`
getChromosomesByOrganism

Description

Function to obtain a list of organisms with their canonical and (when applicable) the autosomal chromosome names. This function is not usually used by the end user directly but through the `filterChromosomes` function.

Usage

```
getChromosomesByOrganism()
```

Value

a list with the organism as keys and the list of available chromosome sets as values

See Also

[getGenome](#), [filterChromosomes](#)

Examples

```
chrsByOrg <- getChromosomesByOrganism()
chrsByOrg[["hg"]]
chrsByOrg[["hg"]][["autosomal"]]
```

`getGenome` *getGenome*

Description

Function to obtain a genome

Usage

```
getGenome(...)
```

Arguments

... a genome parameter is required. The genome object or genome identifier.

Details

If genome is a [BSgenome](#) (from the package BioStrings), it will transform it into a [GRanges](#) with chromosomes and chromosome lengths.

If genome is a [data.frame](#) with 3 columns, it will transform it into a [GRanges](#).

If genome is a [data.frame](#) with 2 columns, it will assume the first is the chromosome, the second is the length of the chromosomes and will add 1 as start.

If genome is a character string uniquely identifying a [BSgenome](#) installed in the system (e.g. "hg19", "mm10",... but not "hg"), it will create a genome based on the [BSgenome](#) object identified by the character string.

If genome is a [GRanges](#) object, it will return it as is.

If genome is non of the above, it will give a warning and try to transform it into a [GRanges](#) using [toGRanges](#). This can be helpful if genome is a connection to a file.

Value

A [GRanges](#) object with the "genome" data c(Chromosome, Start (by default, 1), Chromosome Length) given a [BSgenome](#), a genome name, a [data.frame](#) or a [GRanges](#).

A [GRanges](#) representing the genome with one region per chromosome.

Note

This function is memoised (cached) using the [memoise](#) package. To empty the cache, use [forget](#)(getGenome)

Please note that passing this function the path to a file will not work, since it will assume the character is the identifier of a genome. To read the genome from a file, please use [getGenome](#)([toGRanges](#)("path/to/file"))

See Also

[getMask](#), [getGenomeAndMask](#), [characterToBSgenome](#), [maskFromBSgenome](#), [emptyCacheRegioner](#)

Examples

```
getGenome("hg19")
```

```
getGenome(data.frame(c("chrA", "chrB"), c(15000000, 10000000)))
```

```
getGenomeAndMask
```

```
getGenomeAndMask
```

Description

Function to obtain a valid genome and mask pair given a valid genome identifier and optionally a mask.

If the genome is not a [BSgenome](#) object or a character string uniquely identifying a [BSgenome](#) package installed, it will return the genome "as is". If a mask is provided, it will simply return it. Otherwise it will return the mask returned by [getMask](#)(genome) or an empty mask if genome is not a valid [BSgenome](#) or [BSgenome](#) identifier.

Usage

```
getGenomeAndMask(...)
```

Arguments

... a genome parameter is required, the genome object or genome identifier. A mask parameter is optional: the mask of the genome. If mask is `NULL`, it will try to get a mask from the genome. If mask is `NA` it will return an empty mask.

Value

A list with two elements: genome and mask. Genome and mask are GRanges objects.

Note

This function is memoised (cached) using the `memoise` package. To empty the cache, use `forget(getGenomeAndMask)`

See Also

[getMask](#), [getGenome](#), [characterToBSgenome](#), [maskFromBSgenome](#), [emptyCacheRegionR](#)

Examples

```
getGenomeAndMask("hg19", mask=NA)

getGenomeAndMask(genome=data.frame(c("chrA", "chrB"), c(15000000, 10000000)), mask=NA)
```

getMask

getMask

Description

Function to obtain a mask given a genome available as a `BSgenome`. The mask returned is the merge of all the active masks in the `BSgenome`.

Since it uses `characterToBSgenome`, the genome can be either a `BSgenome` object or a character string uniquely identifying the a `BSgenome` object installed.

Usage

```
getMask(...)
```

Arguments

... a genome parameter is required, the genome from where the mask will be extracted. It can be either a `BSgenome` object or a character string uniquely identifying a `BSgenome` object installed (e.g. "hg19", "mm10", ...)

Value

A [GRanges](#) object with the genomic regions to be masked out

Note

This function is memoised (cached) using the [memoise](#) package. To empty the cache, use [forget](#)(getMask)

See Also

[getGenome](#), [getGenomeAndMask](#), [characterToBSGenome](#), [maskFromBSGenome](#), [emptyCacheRegionR](#)

Examples

```
hg19.mask <- getMask("hg19")
```

```
hg19.mask
```

joinRegions

Join Regions

Description

Joins the regions from a region set A that are less than `min.dist` bases apart.

Usage

```
joinRegions(A, min.dist=1)
```

Arguments

A	a region set in any of the accepted formats by toGRanges (GenomicRanges , data.frame , etc...)
min.dist	an integer indicating the minimum distance required between two regions in order to not fuse them. Any pair of regions closer than <code>min.dist</code> bases will be fused in a larger region. Defaults to 1, so it will only join overlapping regions.

Value

It returns a [GenomicRanges](#) object with the regions resulting from the joining process.

Note

All metadata (additional columns in the region set in addition to chromosome, start and end) will be ignored and not present in the returned region set.

The implementation relies completely in the [reduce](#) function from [IRanges](#) package.

See Also

[plotRegions](#), [toDataframe](#), [toGRanges](#), [subtractRegions](#), [splitRegions](#), [extendRegions](#), [commonRegions](#), [mergeRegions](#), [overlapRegions](#)

Examples

```
A <- data.frame("chr1", c(1, 10, 20, 30), c(12, 13, 28, 40))

join1 <- joinRegions(A)

join2 <- joinRegions(A, min.dist=3)

join3 <- joinRegions(A, min.dist=10)

plotRegions(list(A, join1, join2, join3), chromosome="chr1", regions.labels=c("A", "join1", "join2", "join3"), r
```

listChrTypes *filterChromosomes listChrTypes*

Description

Prints a list of the available organisms and chromosomes sets in the predefined chromosomes sets information.

Usage

```
listChrTypes()
```

Value

the list of available chrs and organisms is printed

See Also

[filterChromosomes](#), [getChromosomesByOrganism](#)

Examples

```
g <- getGenomeAndMask("hg19")$genome

listChrTypes()

g <- filterChromosomes(g, chr.type="autosomal", organism="hg19")
```

localZScore	<i>Local z-score</i>
-------------	----------------------

Description

Evaluates the variation of the z-score in the vicinity of the original region set

Usage

```
localZScore(A, pt, window, step, ...)
```

Arguments

A	a region set in any of the formats accepted by toGRanges (GenomicRanges , data.frame , etc...)
pt	a permTestResult object
window	a window in which the local Z-score will be calculated (bp)
step	the number of bp that divide each Z-score evaluation
...	further arguments to be passed to other methods.

Value

It returns a local z-score object

See Also

[overlapPermTest](#), [permTest](#)

Examples

```
genome <- filterChromosomes(getGenome("hg19"), keep.chr="chr1")
A <- createRandomRegions(nregions=20, length.mean=10000, length.sd=20000, genome=genome, non.overlapping=FALSE)
B <- c(A, createRandomRegions(nregions=10, length.mean=10000, length.sd=20000, genome=genome, non.overlapping=FALSE))

pt <- overlapPermTest(A=A, B=B, ntimes=10, genome=genome, non.overlapping=FALSE)
plot(pt)

lz <- localZScore(A=A, B=B, pt=pt)
plot(lz)
```

maskFromBSGenome	<i>maskFromBSGenome</i>
------------------	-------------------------

Description

Extracts the merge of all the active masks from a [BSgenome](#)

Usage

```
maskFromBSGenome(...)
```

Arguments

... a `bsgenome` parameter is required: a [BSgenome](#) object

Value

A [GRanges](#) object with the active mask in the [BSgenome](#)

Note

This function is memoised (cached) using the [memoise](#) package. To empty the cache, use `forget(maskFromBSGenome)`

See Also

[getGenomeAndMask](#), [characterToBSGenome](#), [emptyCacheRegionER](#)

Examples

```
g <- characterToBSGenome("hg19")
maskFromBSGenome(g)
```

meanDistance	<i>Mean Distance</i>
--------------	----------------------

Description

Computes the mean distance of regions in A to the nearest element in B

Usage

```
meanDistance(A, B, ...)
```

Arguments

- A a region set in any of the accepted formats by `toGRanges` (`GenomicRanges`, `data.frame`, etc...)
- B a region set in any of the accepted formats by `toGRanges` (`GenomicRanges`, `data.frame`, etc...)
- ... any additional parameter needed

Value

The mean of the distances of each region in A to the nearest region in B.

Note

If a region in A is in a chromosome where no B region is, it will be ignored and removed from the mean computation.

Examples

```
A <- data.frame("chr1", c(1, 10, 20, 30), c(12, 13, 28, 40))
B <- data.frame("chr1", 25, 35)
meanDistance(A, B)
```

meanInRegions	<i>Mean In Regions</i>
---------------	------------------------

Description

Returns the mean of a value defined by a region set over another set of regions.

Usage

```
meanInRegions(A, x, col.name=NULL, ...)
```

Arguments

- A a region set in any of the accepted formats by `toGRanges` (`GenomicRanges`, `data.frame`, etc...)
- x a region set in any of the accepted formats with an additional column with a value associated to every region. Regions in x can be points (single base regions).
- col.name character indicating the name of the column. If NULL and if a column with the name "value" exist, it will be used. The 4th column will be used otherwise (or the 5th if 4th is the strand).
- ... any additional parameter needed

Value

It returns a numeric value that is the weighted mean of "value" defined in x over the regions in A. That is, the mean of the value of all regions in x overlapping each region in A weighted according to the number of bases overlapping.

See Also

[permTest](#)

Examples

```
A <- data.frame("chr1", c(1, 10, 20, 30), c(12, 13, 28, 40))
positions <- sample(1:40,30)
x <- data.frame("chr1", positions, positions, rnorm(30,4,1))
meanInRegions(A, x)
x <- GRanges(seqnames=x[,1],ranges=IRanges(x[,2],end=x[,2]),mcols=x[,3])
meanInRegions(A, x)
```

mergeRegions

Merge Regions

Description

Merges the overlapping regions from two region sets. The two region sets are first merged into one and then overlapping regions are fused.

Usage

```
mergeRegions(A, B)
```

Arguments

- A a region set in any of the accepted formats by [toGRanges](#) ([GenomicRanges](#), [data.frame](#), etc...)
- B a region set in any of the accepted formats by [toGRanges](#) ([GenomicRanges](#), [data.frame](#), etc...)

Value

It returns a [GenomicRanges](#) object with the regions resulting from the merging process. Any two overlapping regions from any of the two sets will be fused into one.

Note

All metadata (additional columns in the region set in addition to chromosome, start and end) will be ignored and not present in the returned region set.

The implementation relies completely in the [reduce](#) function from IRanges package.

See Also

[plotRegions](#), [toDataframe](#), [toGRanges](#), [subtractRegions](#), [splitRegions](#), [extendRegions](#), [joinRegions](#), [commonRegions](#), [overlapRegions](#)

Examples

```
A <- data.frame("chr1", c(1, 5, 20, 30), c(8, 13, 28, 40), x=c(1,2,3,4), y=c("a", "b", "c", "d"))
B <- data.frame("chr1", 25, 35)
merges <- mergeRegions(A, B)
plotRegions(list(A, B, merges), chromosome="chr1", regions.labels=c("A", "B", "merges"), regions.colors=3:1)
```

numOverlaps

Number Of Overlaps

Description

Returns the number of regions in A overlapping any region in B

Usage

```
numOverlaps(A, B, count.once=FALSE, ...)
```

Arguments

A	a region set in any of the formats accepted by toGRanges (GenomicRanges , data.frame , etc...)
B	a region set in any of the formats accepted by toGRanges (GenomicRanges , data.frame , etc...)
count.once	boolean indicating whether the overlap of multiple B regions with a single A region should be counted once or multiple times
...	any additional parameters needed

Value

It returns a numeric value that is the number of regions in A overlapping at least one region in B.

See Also

[overlapPermTest](#), [permTest](#)

Examples

```
genome <- filterChromosomes(getGenome("hg19"), keep.chr="chr1")
A <- createRandomRegions(nregions=20, length.mean=10000000, length.sd=20000, genome=genome, non.overlapping=FALSE)
B <- c(A, createRandomRegions(nregions=10, length.mean=10000, length.sd=20000, genome=genome, non.overlapping=FALSE))

numOverlaps(A, B)
numOverlaps(A, B, count.once=TRUE)
```

overlapGraphicalSummary

Overlap Graphical Summary

Description

Graphical summary of the overlap between two set of regions.

Usage

```
overlapGraphicalSummary(A, B, regions.labels=c("A","B"), regions.colors=c("black","forestgreen","darkred"))
```

Arguments

A a region set in any of the accepted formats by [toGRanges](#) ([GenomicRanges](#), [data.frame](#), etc...)

B a region set in any of the accepted formats by [toGRanges](#) ([GenomicRanges](#), [data.frame](#), etc...)

regions.labels vector indicating the labels for the y axes.

regions.colors character vector indicating the colors for the regions.

... Arguments to be passed to methods, such as graphical parameters (see [par](#)).

Value

A plot is created on the current graphics device.

See Also

[overlapPermTest](#), [overlapRegions](#)

Examples

```
A <- data.frame(chr=1, start=c(1,15,24,40,50), end=c(10,20,30,45,55))
B <- data.frame(chr=1, start=c(2,12,28,35), end=c(5,25,33,43))

overlapGraphicalSummary(A, B, regions.labels=c("A","B"), regions.colors=c(4,5,6))
```

overlapPermTest	<i>Permutation Test for Overlap</i>
-----------------	-------------------------------------

Description

Performs a permutation test to see if there is an association in overlap between a region set A and a region set B creating random regions through the genome.

Usage

```
overlapPermTest (A, B, alternative="auto", ...)
```

Arguments

A	a region set in any of the accepted formats by toGRanges (GenomicRanges , data.frame , etc...)
B	a region set in any of the accepted formats by toGRanges (GenomicRanges , data.frame , etc...)
alternative	the alternative hypothesis must be one of "greater", "less" or "auto". If "auto", the alternative will be decided depending on the data.
...	further arguments to be passed to or from methods.

Value

A list of class permTestResults containing the following components:

- pval the p-value of the test.
- ntimes the number of permutations.
- alternative a character string describing the alternative hypothesis.
- observed the value of the statistic for the original data set.
- permuted the values of the statistic for each permuted data set.
- zscore the value of the standard score. $(\text{observed} - \text{mean}(\text{permuted})) / \text{sd}(\text{permuted})$

See Also

[overlapGraphicalSummary](#), [overlapRegions](#), [toDataframe](#), [toGRanges](#), [permTest](#)

Examples

```
genome <- filterChromosomes(getGenome("hg19"), keep.chr="chr1")
A <- createRandomRegions(nregions=20, length.mean=1000000, length.sd=20000, genome=genome, non.overlapping=FALSE)
B <- c(A, createRandomRegions(nregions=10, length.mean=10000, length.sd=20000, genome=genome, non.overlapping=FALSE))

pt <- overlapPermTest(A=A, B=B, ntimes=10, genome=genome, non.overlapping=FALSE, verbose=TRUE)
summary(pt)
plot(pt)
plot(pt, plotType="Tailed")
```

overlapRegions	<i>Overlap Regions</i>
----------------	------------------------

Description

return overlap between 2 regio set A and B

Usage

```
overlapRegions(A, B, colA=NULL, colB=NULL, type="any", min.bases=1, min.pctA=NULL, min.pctB=NULL, get
```

Arguments

A	a region set in any of the accepted formats by toGRanges (GenomicRanges , data.frame , etc...)
B	a region set in any of the accepted formats by toGRanges (GenomicRanges , data.frame , etc...)
colA	numeric vector indicating which columns of A the results will contain (default NULL)
colB	numeric vector indicating which columns of B the results will contain (default NULL)
type	<ul style="list-style-type: none"> • AinB: the region in A is contained in a region in B • BinA: the region in B is contained in A • within: the region in A or B is contained in a region in the other region set • equal: the region in A has the same chromosome, start and end as a region in B • AleftB: the end of the region from A overlaps the beginning of a region in B • ArightB: the start of a region from A overlaps the end of a region in B • any: any kind of overlap is returned
min.bases	numeric minimum number of bp accepted to define a overlap (default 1)
min.pctA	numeric minimum percentage of bases of A accepted to define a overlap (default NULL)
min.pctB	numeric minimum percentage of bases of B accepted to define a overlap (default NULL)
get.pctA	boolean if TRUE add a column in the results indicating the number percentage of A are involved in the overlap (default FALSE)
get.pctB	boolean if TRUE add a column in the results indicating the number percentage of B are involved in the overlap (default FALSE)
get.bases	boolean if TRUE add in the results the number of overlapped bases (default FALSE)
only.boolean	boolean if TRUE devolve as result a boolean vector containing the overlap state of each regions of A (default FALSE)

only.count boolean if TRUE devolve as result the number of regions of A overlapping with B

... any additional parameter (are there any left?)

Value

the default results is a `data.frame` with at least 5 columns "chr" indicating the chromosome of the appartenance of each overlap, "startA", "endA", "startB", "endB", indicating the coordinates of the region A and B for each overlap "type" that describe the nature of the overlap (see arguments "type") eventually other columns can be added (see see arguments "colA", "colB", "get.pctA", "get.pctB", "get.bases")

Note

The implementation uses when possible the `countOverlaps` function from IRanges package.

See Also

[plotRegions](#), [toDataframe](#), [toGRanges](#), [subtractRegions](#), [splitRegions](#), [extendRegions](#), [commonRegions](#), [mergeRegions](#), [joinRegions](#)

Examples

```
A <- data.frame("chr1", c(1, 5, 20, 30), c(8, 13, 28, 40), x=c(1,2,3,4), y=c("a", "b", "c", "d"))
B <- data.frame("chr1", 25, 35)
overlapRegions(A, B)
```

permTest

Permutation Test

Description

Performs a permutation test to see if there is an association between a region set and some other feature using an evaluation function. #'

Usage

```
permTest(A, ntimes=100, randomize.function, evaluate.function, alternative="auto", min.parallel=1000)
```

Arguments

A a region set in any of the accepted formats by `toGRanges` (`GenomicRanges`, `data.frame`, etc...)

ntimes number of permutations

randomize.function function to create random regions. It must return a set of regions.

evaluate.function	function to search for association. It must return a numeric value.
alternative	the alternative hypothesis must be one of "greater", "less" or "auto". If "auto", the alternative will be decided depending on the data.
min.parallel	if force.parallel is not specified, this will be used to determine the threshold for parallel computation. If $\text{length}(A) * \text{ntimes} > \text{min.parallel}$, it will activate the parallel computation. Single threaded otherwise.
force.parallel	logical indicating if the computation must be paralelized.
randomize.function.name	character. If specified, the permTestResults object will have this name instead of the name of the randomization function used. Useful specially when using unnamed anonymous functions.
evaluate.function.name	character. If specified, the permTestResults object will have this name instead of the name of the evaluation function used. Useful specially when using unnamed anonymous functions.
verbose	a boolean. If verbose=TRUE it creates a progress bar to show the computation progress. When combined with parallel computation, it might have an impact in the total computation time.
...	further arguments to be passed to other methods.

Details

permTest performs a permutation test of the regions in RS to test the association with the feature evaluated with the evaluation function. The regions are randomized using the randomization.function and the evaluation.function is used to evaluate them. More information can be found in the vignette.

Value

A list of class permTestResults containing the following components:

- pval the p-value of the test.
- ntimes the number of permutations.
- alternative a character string describing the alternative hypotesis.
- observed the value of the statistic for the original data set.
- permuted the values of the statistic for each permuted data set.
- zscore the value of the standard score. $(\text{observed} - \text{mean}(\text{permuted})) / \text{sd}(\text{permuted})$
- randomize.function the randomization function used.
- randomize.function.name the name of the randomization used.
- evaluate.function the evaluation function used.
- evaluate.function.name the name of the evaluation function used.

References

Davison, A. C. and Hinkley, D. V. (1997) Bootstrap methods and their application, Cambridge University Press, United Kingdom, 156-160

See Also

[overlapPermTest](#)

Examples

```
genome <- filterChromosomes(getGenome("hg19"), keep.chr="chr1")
A <- createRandomRegions(nregions=20, length.mean=10000000, length.sd=20000, genome=genome, non.overlapping=FALSE)
B <- c(A, createRandomRegions(nregions=10, length.mean=10000, length.sd=20000, genome=genome, non.overlapping=FALSE))

pt2 <- permTest(A=A, B=B, ntimes=10, alternative="auto", verbose=TRUE, genome=genome, evaluate.function=meanDistance)
summary(pt2)
plot(pt2)
plot(pt2, plotType="Tailed")
```

`plot.permTestResults` *Function for plotting the results from a permTestResults object.*

Description

Function for plotting the results from a permTestResults object.

Usage

```
## S3 method for class 'permTestResults'
plot(x, pvalthres = 0.05, plotType = "Tailed",
     main = "", xlab = NULL, ylab = "", ...)
```

Arguments

<code>x</code>	an object of class <code>permTestResults</code> .
<code>pvalthres</code>	p-value threshold for significance. Default is 0.05.
<code>plotType</code>	the type of plot to display. This must be one of "Area" or "Tailed". Default is "Area".
<code>main</code>	a character specifying the title of the plot. Defaults to "".
<code>xlab</code>	a character specifying the label of the x axis. Defaults to NULL, which produces a plot with the evaluation function name as the x axis label.
<code>ylab</code>	a character specifying the label of the y axis. Defaults to "".
<code>...</code>	further arguments to be passed to or from methods.

Value

A plot is created on the current graphics device.

See Also

[permTest](#)

Examples

```
genome <- filterChromosomes(getGenome("hg19"), keep.chr="chr1")
A <- createRandomRegions(nregions=20, length.mean=10000000, length.sd=20000, genome=genome, non.overlapping=FALSE)
B <- c(A, createRandomRegions(nregions=10, length.mean=10000, length.sd=20000, genome=genome, non.overlapping=FALSE))

pt <- overlapPermTest(A=A, B=B, ntimes=10, genome=genome, non.overlapping=FALSE)
summary(pt)
plot(pt)
plot(pt, plotType="Tailed")

pt2 <- permTest(A=A, B=B, ntimes=10, alternative="auto", genome=genome, evaluate.function=meanDistance, randomize=TRUE)
summary(pt2)
plot(pt2)
plot(pt2, plotType="Tailed")
```

plotRegions

Plot Regions

Description

Plots sets of regions

Usage

```
plotRegions(x, chromosome, start=NULL, end=NULL, regions.labels=NULL, regions.colors=NULL, ...)
```

Arguments

x	list of objects to be plotted.
chromosome	character or numeric value indicating which chromosome you want to plot.
start	numeric value indicating from which position you want to plot.
end	numeric value indicating to which position you want to plot.
regions.labels	vector indicating the labels for the y axes. It must have the same length as x.
regions.colors	character vector indicating the colors for the plotted regions. It must have the same length as x.
...	Arguments to be passed to methods, such as graphical parameters (see par).

Value

A plot is created on the current graphics device.

Examples

```
A <- data.frame(chr=1, start=c(1,15,24,40,50), end=c(10,20,30,45,55))
B <- data.frame(chr=1, start=c(2,12,28,35), end=c(5,25,33,43))
plotRegions(list(A,B), chromosome=1, regions.labels=c("A","B"), regions.colors=3:2)
```

randomizeRegions	<i>Randomize Regions</i>
------------------	--------------------------

Description

Given a set of regions A and a genome, this function returns a new set of regions randomly distributed in the genome.

Usage

```
randomizeRegions(A, genome="hg19", mask=NULL, non.overlapping=TRUE, per.chromosome=FALSE, ...)
```

Arguments

A	The set of regions to randomize. A region set in any of the accepted formats by toGRanges (GenomicRanges , data.frame , etc...)
genome	The reference genome to use. A valid genome object. Either a GenomicRanges or data.frame containing one region per whole chromosome or a character uniquely identifying a genome in BSgenome (e.g. "hg19", "mm10",... but not "hg"). Internally it uses getGenomeAndMask .
mask	The set of regions specifying where a random region can not be (centromeres, repetitive regions, unmappable regions...). A region set in any of the accepted formats by toGRanges (GenomicRanges , data.frame , ...). If <code>NULL</code> it will try to derive a mask from the genome (currently only works if the genome is a character string). If <code>NA</code> it gives, explicitly, an empty mask.
non.overlapping	A boolean stating whether the random regions can overlap (<code>FALSE</code>) or not (<code>TRUE</code>).
per.chromosome	Boolean. If <code>TRUE</code> , the regions will be created in a per chromosome maner - every region in A will be moved into a random position at the same chromosome where it was originally-.
...	further arguments to be passed to or from methods.

Details

The new set of regions will be created with the same sizes of the original ones, and optionally placed in the same chromosomes.

In addition, they can be made explicitly non overlapping and a mask can be provided so no regions fall in an undesirable part of the genome.

Value

It returns a [GenomicRanges](#) object with the regions resulting from the randomization process.

See Also

[toDataframe](#), [toGRanges](#), [getGenome](#), [getMask](#), [getGenomeAndMask](#), [characterToBSGenome](#), [maskFromBSGenome](#), [resampleRegions](#), [createRandomRegions](#), [circularRandomizeRegions](#)

Examples

```
A <- data.frame("chr1", c(1, 10, 20, 30), c(12, 13, 28, 40))
mask <- data.frame("chr1", c(20000000, 100000000), c(22000000, 130000000))
genome <- data.frame(c("chr1", "chr2"), c(1, 1), c(180000000, 200000000))
randomizeRegions(A)
randomizeRegions(A, genome=genome, mask=mask, per.chromosome=TRUE, non.overlapping=TRUE)
```

recomputePermTest	<i>Recompute Permutation Test</i>
-------------------	-----------------------------------

Description

Recomputes the permutation test changing the alternative hypothesis

Usage

```
recomputePermTest(ptr)
```

Arguments

ptr an object of class permTestResults

Value

A list of class permTestResults containing the same components as [permTest](#) results.

See Also

[permTest](#)

Examples

```

A <- createRandomRegions(nregions=10, length.mean=1000000)

B <- createRandomRegions(nregions=10, length.mean=1000000)

resPerm <- permTest(A=A, B=B, ntimes=5, alternative="less", genome="hg19", evaluate.function=meanDistance, randomizeRegions=TRUE)

plot(resPerm)

resPermRecomputed <- recomputePermTest(resPerm)

summary(resPermRecomputed)

plot(resPermRecomputed)

```

resampleRegions	<i>Resample Regions</i>
-----------------	-------------------------

Description

Function for sampling a region set from a univers of region sets.

Usage

```
resampleRegions(A, universe, per.chromosome=FALSE, ...)
```

Arguments

A	a region set in any of the formats accepted by toGRanges (GenomicRanges , data.frame , etc...)
universe	a region set in any of the formats accepted by toGRanges (GenomicRanges , data.frame , etc...)
per.chromosome	boolean indicating if sample must be by chromosome.
...	further arguments to be passed to or from methods.

Value

a [GenomicRanges](#) object. A sample from the univers with the same length as A.

See Also

[toDataframe](#), [toGRanges](#), [randomizeRegions](#), [createRandomRegions](#)

Examples

```
universe <- data.frame(chr=1, start=c(1,15,24,40,50), end=c(10,20,30,45,55))
A <- data.frame(chr=1, start=c(2,12,28,35), end=c(5,25,33,43))
resampleRegions(A, universe, per.chromosome=TRUE)
```

splitRegions

*Split Regions***Description**

Splits a region set A by both ends of the regions in a second region set B.

Usage

```
splitRegions(A, B, min.size=1, track.original=TRUE)
```

Arguments

A	a region set in any of the formats accepted by toGRanges (GenomicRanges , data.frame , etc...)
B	a region set in any of the formats accepted by toGRanges (GenomicRanges , data.frame , etc...)
min.size	numeric value, minimal size of the new regions
track.original	logical indicating if you want to keep the original regions and additional information in the output

Value

A GRanges with the splitted regions.

See Also

[toDataframe](#), [toGRanges](#), [subtractRegions](#), [commonRegions](#), [extendRegions](#), [joinRegions](#), [mergeRegions](#), [overlapRegions](#)

Examples

```
A <- data.frame(chr=1, start=c(1, 15, 24, 40, 50), end=c(10, 20, 30, 45, 55))
B <- data.frame(chr=1, start=c(2, 12, 28, 35), end=c(5, 25, 33, 43))
splits <- splitRegions(A, B)
plotRegions(list(A, B, splits), chromosome=1, regions.labels=c("A", "B", "splits"), regions.colors=3:1)
```

subtractRegions	<i>Subtract Regions</i>
-----------------	-------------------------

Description

Function for subtracting a region set from another region set.

Usage

```
subtractRegions(A, B)
```

Arguments

- A a region set in any of the accepted formats by `toGRanges` (`GenomicRanges`, `data.frame`, etc...)
- B a region set in any of the accepted formats by `toGRanges` (`GenomicRanges`, `data.frame`, etc...)

Details

This function returns the regions in A minus the parts of them overlapping the regions in B. Overlapping regions in the result will be fused.

The implementation relies completely in the `setdiff` function from `IRanges` package.

Value

A `GenomicRanges` object

Examples

```
A <- data.frame(chr=1, start=c(1, 15, 24, 31), end=c(10, 20, 30, 35))
B <- data.frame(chr=1, start=c(2, 12, 24, 35), end=c(5, 25, 29, 40))
subtract <- subtractRegions(A, B)

plotRegions(list(A, B, subtract), chromosome=1, regions.labels=c("A", "B", "subtract"), regions.colors=3:1)
```

toDataframe	<i>toDataframe</i>
-------------	--------------------

Description

Transforms a [GRanges](#) object or a `data.frame` containing a region set into a `data.frame`.

Usage

```
toDataframe(A, stranded=FALSE)
```

Arguments

`A` a [GRanges](#) object.

`stranded` (only used when `A` is a [GRanges](#) object) a logical indicating whether a column with the strand information have to be added to the result (Defaults to `FALSE`)

Details

If the object is of class `data.frame`, it will be returned untouched.

Value

A `data.frame` with the regions in `A`. If `A` was a [GRanges](#) object, the output will include any metadata present in `A`.

See Also

[toGRanges](#)

Examples

```
A <- data.frame(chr=1, start=c(1, 15, 24), end=c(10, 20, 30), x=c(1,2,3), y=c("a", "b", "c"))
A2 <- toGRanges(A)
toDataframe(A2)
```

`toGRanges`*toGRanges*

Description

Transforms a file or an object containing a region set into a [GRanges](#) object.

Usage

```
toGRanges(A, ...)
```

Arguments

`A` a [data.frame](#) containing a region set, a [GRanges](#) object, a BED file or any type of file supported by `rtracklayer`

`...` further arguments to be passed to other methods.

Details

If `A` is already a [GRanges](#) object, it will be returned untouched.

If `A` is a file name or connection to a file in any of the formats supported by `rtracklayer`'s `import` function (BED, GFF...) it will be imported using `rtracklayer`.

If `A` is a data frame, the function will assume the first three columns are chromosome, start and end and create a [GRanges](#) object. Any additional column will be considered metadata and stored as such in the [GRanges](#) object.

Value

A [GRanges](#) object with the regions in `A`

See Also

[toDataframe](#)

Examples

```
A <- data.frame(chr=1, start=c(1, 15, 24), end=c(10, 20, 30), x=c(1,2,3), y=c("a", "b", "c"))
toGRanges(A)
```

uniqueRegions	<i>Unique Regions</i>
---------------	-----------------------

Description

Returns the regions unique to only one of the two region sets, that is, all parts of the genome covered by only one of the two region sets.

Usage

```
uniqueRegions(A, B)
```

Arguments

A a region set in any of the accepted formats by [toGRanges](#) ([GenomicRanges](#), [data.frame](#), etc...)

B a region set in any of the accepted formats by [toGRanges](#) ([GenomicRanges](#), [data.frame](#), etc...)

Value

It returns a [GenomicRanges](#) object with the regions unique to one of the region sets.

Note

All metadata (additional columns in the region set in addition to chromosome, start and end) will be ignored and not present in the returned region set.

See Also

[toGRanges](#), [subtractRegions](#), [commonRegions](#), [mergeRegions](#)

Examples

```
A <- data.frame("chr1", c(1, 10, 20, 30), c(12, 13, 28, 40))
B <- data.frame("chr1", 25, 35)
uniques <- uniqueRegions(A, B)

plotRegions(list(A, B, uniques), chromosome="chr1", regions.labels=c("A", "B", "uniques"), regions.colors=3:1)
```

Index

BSgenome, [2](#), [3](#), [5](#), [8](#), [10](#), [11](#), [15](#), [26](#)

characterToBSGenome, [2](#), [4](#), [6](#), [10–12](#), [15](#), [27](#)

circularRandomizeRegions, [3](#), [27](#)

commonRegions, [4](#), [7](#), [13](#), [18](#), [22](#), [29](#), [33](#)

countOverlaps, [22](#)

createRandomRegions, [4](#), [5](#), [27](#), [28](#)

data.frame, [3–5](#), [7](#), [8](#), [10](#), [12](#), [14](#), [16–22](#), [26](#), [28–33](#)

emptyCacheRegioner, [6](#), [10–12](#), [15](#)

extendRegions, [5](#), [7](#), [13](#), [18](#), [22](#), [29](#)

filterChromosomes, [8](#), [9](#), [13](#)

forget, [10–12](#), [15](#)

GenomicRanges, [3–8](#), [12](#), [14](#), [16–22](#), [26–30](#), [33](#)

getChromosomesByOrganism, [8](#), [9](#), [13](#)

getGenome, [4](#), [6](#), [9](#), [9](#), [11](#), [12](#), [27](#)

getGenomeAndMask, [3–6](#), [8](#), [10](#), [10](#), [12](#), [15](#), [26](#), [27](#)

getMask, [4](#), [6](#), [10](#), [11](#), [11](#), [27](#)

GRanges, [8](#), [10](#), [12](#), [15](#), [31](#), [32](#)

joinRegions, [5](#), [7](#), [12](#), [18](#), [22](#), [29](#)

listChrTypes, [8](#), [13](#)

localZScore, [14](#)

maskFromBSGenome, [3](#), [4](#), [6](#), [10–12](#), [15](#), [27](#)

mean, [20](#), [23](#)

meanDistance, [15](#)

meanInRegions, [16](#)

memoise, [10–12](#), [15](#)

mergeRegions, [5](#), [7](#), [13](#), [17](#), [22](#), [29](#), [33](#)

NA, [3](#), [5](#), [11](#), [26](#)

NULL, [3](#), [5](#), [11](#), [26](#)

numOverlaps, [18](#)

overlapGraphicalSummary, [19](#), [20](#)

overlapPermTest, [14](#), [19](#), [20](#), [24](#)

overlapRegions, [5](#), [7](#), [13](#), [18–20](#), [21](#), [29](#)

par, [19](#), [25](#)

permTest, [14](#), [17](#), [19](#), [20](#), [22](#), [25](#), [27](#)

plot.permTestResults, [24](#)

plotRegions, [5](#), [7](#), [13](#), [18](#), [22](#), [25](#)

randomizeRegions, [4](#), [6](#), [26](#), [28](#)

recomputePermTest, [27](#)

reduce, [12](#), [18](#)

resampleRegions, [4](#), [6](#), [27](#), [28](#)

sd, [20](#), [23](#)

splitRegions, [5](#), [7](#), [13](#), [18](#), [22](#), [29](#)

subtractRegions, [5](#), [7](#), [13](#), [18](#), [22](#), [29](#), [30](#), [33](#)

toDataframe, [4](#), [5](#), [7](#), [13](#), [18](#), [20](#), [22](#), [27–29](#), [31](#), [32](#)

toGRanges, [3–5](#), [7](#), [8](#), [10](#), [12–14](#), [16–22](#), [26–31](#), [32](#), [33](#)

uniqueRegions, [33](#)