

Package ‘PoTRA’

March 30, 2021

Type Package

Title PoTRA: Pathways of Topological Rank Analysis

Version 1.6.0

Author Chaoxing Li, Li Liu and Valentin Dinu

Maintainer Valentin Dinu <valentin.dinu@asu.edu>

Description The PoTRA analysis is based on topological ranks of genes in biological pathways. PoTRA can be used to detect pathways involved in disease (Li, Liu & Dinu, 2018). We use PageRank to measure the relative topological ranks of genes in each biological pathway, then select hub genes for each pathway, and use Fishers Exact test to determine if the number of hub genes in each pathway is altered from normal to cancer (Li, Liu & Dinu, 2018). Alternatively, if the distribution of topological ranks of gene in a pathway is altered between normal and cancer, this pathway might also be involved in cancer (Li, Liu & Dinu, 2018). Hence, we use the Kolmogorov–Smirnov test to detect pathways that have an altered distribution of topological ranks of genes between two phenotypes (Li, Liu & Dinu, 2018). PoTRA can be used with the KEGG, Biocarta, Reactome, NCI, SMPDB and PharmGKB databases from the devel graphite library.

License LGPL

Encoding UTF-8

LazyData false

Depends R (>= 3.6.0), stats, BiocGenerics, org.Hs.eg.db, igraph, graph, graphite

Imports

biocViews GraphAndNetwork, StatisticalMethod, GeneExpression, DifferentialExpression, Pathways, Reactome, Network, KEGG, BioCarta

RoxygenNote 6.1.1

Suggests BiocStyle, knitr, rmarkdown, colr, metap, repmis

VignetteBuilder knitr

git_url <https://git.bioconductor.org/packages/PoTRA>

git_branch RELEASE_3_12

git_last_commit 8260972

git_last_commit_date 2020-10-27

Date/Publication 2021-03-29

R topics documented:

PoTRA 2

Index **3**

PoTRA *PoTRA.corN*

Description

The PoTRA analysis is based on topological ranks of genes in biological pathways. PoTRA can be used to detect pathways involved in disease. The PoTRA package contains one function for creating the PoTRA results object.

Usage

```
PoTRA.corN(mydata, genelist, Num.sample.normal, Num.sample.case, Pathway.database, PR.quantile)
```

Arguments

mydata	Dataframe that contains rownames consisting of entrez gene identifiers and columns representing normals and samples from gene expression data.
genelist	Dataframe that consists of a single column of entrez gene identifiers (the same as those found in the rownames(mydata)).
Num.sample.normal	Represents normal samples in the mydata dataframe.
Num.sample.case	Represents case samples in the mydata dataframe.
Pathway.database	Object contains gene lists from KEGG, Reactome, Biocarta and PharmGKB databases, and these are made available through the devel graphite library.
PR.quantile	Object contains the percentile of PageRank scores as a cutoff for hub genes, the recommended percentile is 0.95.

Author(s)

Chaoxing Li, Li Liu, Valentine Dinu <valentine.dinu@asu.edu>

Index

PoTRA, 2