

# Package ‘cellbaseR’

September 21, 2017

**Type** Package

**Date** 2016-04-17

**Title** Querying annotation data from the high performance Cellbase web services

**Version** 1.0.0

**Author** Mohammed OE Abdallah

**Maintainer** Mohammed OE Abdallah <melsiddieg@gmail.com>

**URL** <https://github.com/melsiddieg/cellbaseR>

**Description** This R package makes use of the exhaustive RESTful Web service API that has been implemented for the Cellbase database. It enable researchers to query and obtain a wealth of biological information from a single database saving a lot of time. Another benefit is that researchers can easily make queries about different biological topics and link all this information together as all information is integrated.

**License** Apache License (== 2.0)

**Depends** R(>= 3.4)

**Imports** methods, jsonlite, httr, data.table, pbapply, tidyr, R.utils, Rsamtools, BiocParallel, foreach, utils, parallel, doParallel

**Suggests** BiocStyle, knitr, rmarkdown, Gviz, VariantAnnotation

**RoxygenNote** 6.0.1

**biocViews** Annotation, VariantAnnotation

**Lazy** TRUE

**LazyData** TRUE

**Collate** 'commons.R' 'AllClasses.R' 'AllGenerics.R'  
'AnnotateVcf-methods.R' 'CellBaseParam-methods.R'  
'CellBaseR-methods.R' 'cellbase.R' 'getCellbase-methods.R'  
'getChromosomeInfo-methods.R' 'getClinical-methods.R'  
'getGene-methods.R' 'getMeta-methods.R' 'getProtein-methods.R'  
'getRegion-methods.R' 'getSnps-methods.R' 'getTf-methods.R'  
'getTranscript-methods.R' 'getVariant-methods.R'  
'getXref-methods.R' 'show-methods.R' 'tools.R' 'user.R'

**VignetteBuilder** knitr

**NeedsCompilation** no

## R topics documented:

cellbaseR-package	2
AnnotateVcf,CellBaseR-method	3
CellBaseParam	4
CellBaseParam-class	5
CellBaseR	5
CellBaseR-class	6
createGeneModel	7
getCaddScores	8
getCellBase,CellBaseR-method	8
getCellBaseResourceHelp	9
getChromosomeInfo,CellBaseR-method	10
getClinical,CellBaseR-method	11
getClinicalByGene	12
getClinicalByRegion	12
getConservationByRegion	13
getGene,CellBaseR-method	13
getGeneInfo	14
getMeta,CellBaseR-method	15
getProtein,CellBaseR-method	15
getProteinInfo	16
getRegion,CellBaseR-method	17
getRegulatoryByRegion	18
getSnp,CellBaseR-method	18
getSnpByGene	19
getTf,CellBaseR-method	20
getTfbsByRegion	21
getTranscript,CellBaseR-method	21
getTranscriptByGene	22
getVariant,CellBaseR-method	23
getVariantAnnotation	24
getXref,CellBaseR-method	24
<b>Index</b>	<b>26</b>

---

cellbaseR-package	<i>cellbaseR</i>
-------------------	------------------

---

### Description

Querying annotation data from the high performance Cellbase web services

### Details

Documentation for the cellbaseR package

This R package makes use of the exhaustive RESTful Web service API that has been implemented for the Cellbase database. It enables researchers to query and obtain a wealth of biological information from a single database saving a lot of time. Another benefit is that researchers can easily make queries about different biological topics and link all this information together as all information is integrated. Currently Homo sapiens, Mus musculus and other 20 species are available and many others will be included soon. Results returned from the cellbase queries are parsed into R data.frames and other common R data structures so users can readily get into downstream analysis.

**Author(s)**

Mohammed OE Abdallah

**See Also**

Useful links:

- <https://github.com/melsiddieg/cellbaseR>

---

AnnotateVcf,CellBaseR-method

*AnnotateVcf*

---

**Description**

This method is a convenience method to annotate bgzipped tabix-indexed vcf files. It should be ideal for annotating small to medium sized vcf files.

**Usage**

```
## S4 method for signature 'CellBaseR'  
AnnotateVcf(object, file, batch_size, num_threads,  
            BPPARAM = bpparam())
```

**Arguments**

object	an object of class CellBaseR
file	Path to a bgzipped and tabix indexed vcf file
batch_size	integer if multiple queries are raised by a single method call, e.g. getting annotation info for several genes, queries will be sent to the server in batches. This slot indicates the size of each batch, e.g. 200
num_threads	number of asynchronous batches to be sent to the server
BPPARAM	a BiocParallel class object

**Value**

a dataframe with the results of the query

**See Also**

<https://github.com/opencb/cellbase/wiki> and the RESTful API documentation <http://bioinfo.hpc.cam.ac.uk/cellbase/webservices/>

**Examples**

```
cb <- CellBaseR()  
fl <- system.file("extdata", "hapmap_exome_chr22_500.vcf.gz",  
                 package = "cellbaseR" )  
res <- AnnotateVcf(object=cb, file=fl, BPPARAM = bpparam(workers=2))
```

---

CellBaseParam

*A Constructor for the CellBaseParam Object*

---

## Description

CellBaseParam object is used to control what results are returned from the CellBaseR methods

## Usage

```
CellBaseParam(genome = character(), gene = character(),
  region = character(), rs = character(), so = character(),
  phenotype = character(), include = character(), exclude = character(),
  limit = character())
```

## Arguments

genome	A character denoting the genome build to query, eg, GRCh37 (default), or GRCh38
gene	A character vector denoting the gene/s to be queried
region	A character vector denoting the region/s to be queried must be in the form 1:100000-1500000 not chr1:100000-1500000
rs	A character vector denoting the rs ids to be queried
so	A character vector denoting sequence ontology to be queried
phenotype	A character vector denoting the phenotype to be queried
include	A character vector denoting the fields to be returned
exclude	A character vector denoting the fields to be excluded
limit	A number limiting the number of results to be returned

## Value

an object of class CellBaseParam

## See Also

<https://github.com/opencb/cellbase/wiki> and the RESTful API documentation <http://bioinfo.hpc.cam.ac.uk/cellbase/webservices/>

## Examples

```
cbParam <- CellBaseParam(genome="GRCh38", gene=c("TP73", "TET1"))
print(cbParam)
```

---

CellBaseParam-class	<i>CellBaseParam Class</i>
---------------------	----------------------------

---

### Description

This class defines a CellBaseParam object to hold filtering parameters.

### Details

This class stores parameters used for filtering the CellBaseR query and is available for all query methods. CellBaseParam object is used to control what results are returned from the CellBaseR methods

### Slots

genome A character the genome build to query, e.g.GRCh37(default)

gene A character vector denoting the gene/s to be queried

region A character vector denoting the region/s to be queried must be in the form 1:100000-150000

rs A character vector denoting the rs ids to be queried

so A character vector denoting sequence ontology to be queried

phenotype A character vector denoting the phenotype to be queried

include A character vector denoting the fields to be returned

exclude A character vector denoting the fields to be excluded

limit A number limiting the number of results to be returned

### See Also

<https://github.com/opencb/cellbase/wiki> and the RESTful API documentation <http://bioinfo.hpc.cam.ac.uk/cellbase/webservices/>

---

CellBaseR	<i>CellBaseR</i>
-----------	------------------

---

### Description

This is a constructor function for the CellBaseR object

### Usage

```
CellBaseR(host = "http://bioinfo.hpc.cam.ac.uk/cellbase/webservices/rest/",
  version = "v4", species = "hsapiens", batch_size = 200L,
  num_threads = 8L)
```

**Arguments**

host	A character the default host url for cellbase webservices, e.g. "http://bioinfo.hpc.cam.ac.uk/cellbase/w
version	A character the cellbae API version, e.g. "V4"
species	a character specifying the species to be queried, e.g. "hsapiens"
batch_size	intger if multiple queries are raised by a single method call, e.g. getting annota- tion info for several genes, queries will be sent to the server in batches.This slot indicates the size of each batch,e.g. 200
num_threads	integer number of batches to be sent to the server

**Details**

CellbaseR constructor function

This class defines the CellBaseR object. It holds the default configuration required by CellBaseR methods to connect to the cellbase web services. By defult it is configured to query human data based on the GRCh37 genome assembly.

**Value**

An object of class CellBaseR

**See Also**

<https://github.com/opencb/cellbase/wiki> and the RESTful API documentation <http://bioinfo.hpc.cam.ac.uk/cellbase/webservices/>

**Examples**

```
cb <- CellBaseR()
print(cb)
```

---

CellBaseR-class

*CellBaseR Class*

---

**Description**

This is an S4 class which defines the CellBaseR object

**Details**

This S4 class holds the default configuration required by CellBaseR methods to connect to the cellbase web services. By default it is configured to query human data based on the GRCh37 genome assembly.

**Slots**

host a character specifying the host url. Default "http://bioinfo.hpc.cam.ac.uk/cellbase/webservices/rest/"  
 version a character specifying the API version. Default "v4"  
 species a character specifying the species to be queried. Default "hsapiens"  
 batch\_size if multiple queries are raised by a single method call, e.g. getting annotation info for  
 several genes, queries will be sent to the server in batches. This slot indicates the size of these  
 batches. Default 200  
 num\_threads the number of threads. Default 8

**See Also**

<https://github.com/opencb/cellbase/wiki> and the RESTful API documentation <http://bioinfo.hpc.cam.ac.uk/cellbase/webservices/>

---

createGeneModel	<i>createGeneModel</i>
-----------------	------------------------

---

**Description**

A convenience function to construct a gene model

**Usage**

```
createGeneModel(object, region = NULL)
```

**Arguments**

object	an object of class CellbaseResponse
region	a character

**Details**

This function creates a gene model data frame, which can be then turned into a GeneRegionTrack for visualization by [GeneRegionTrack](#)

**Value**

A geneModel

**See Also**

<https://github.com/opencb/cellbase/wiki> and the RESTful API documentation <http://bioinfo.hpc.cam.ac.uk/cellbase/webservices/>

**Examples**

```
cb <- CellBaseR()
test <- createGeneModel(object = cb, region = "17:1500000-1550000")
```

---

<code>getCaddScores</code>	<i>getCaddScores</i>
----------------------------	----------------------

---

**Description**

A convenience method to fetch Cadd scores for specific variant/s

**Usage**

```
getCaddScores(object, id, param = NULL)
```

**Arguments**

<code>object</code>	an object of class <code>CellBaseR</code>
<code>id</code>	a character vector of genomic variants, eg 19:45411941:T:C
<code>param</code>	an object of class <code>CellBaseParam</code>

**Value**

a dataframe of the query result

**Examples**

```
cb <- CellBaseR()
res <- getCaddScores(cb, "19:45411941:T:C")
```

---

<code>getCellBase,CellBaseR-method</code>	<i>getCellBase</i>
---	--------------------

---

**Description**

The generic method for querying CellBase web services.

**Usage**

```
## S4 method for signature 'CellBaseR'
getCellBase(object, category, subcategory, ids, resource,
  param = NULL)
```

**Arguments**

<code>object</code>	an object of class <code>CellBaseR</code>
<code>category</code>	character to specify the category to be queried.
<code>subcategory</code>	character to specify the subcategory to be queried
<code>ids</code>	a character vector of the ids to be queried
<code>resource</code>	a character to specify the resource to be queried
<code>param</code>	an object of class <code>CellBaseParam</code> specifying additional param for the <code>CellBaseR</code>



**Details**

This method allows the user to query the cellbase web services without any predefined categories, subcategories, or resources.

**Value**

a dataframe holding the results of the query

**See Also**

<https://github.com/opencb/cellbase/wiki> and the RESTful API documentation <http://bioinfo.hpc.cam.ac.uk/cellbase/webservices/>

**Examples**

```
cb <- CellBaseR()
res <- getCellBase(object=cb, category="feature", subcategory="gene",
ids="TET1", resource="info")
```

---

getCellBaseResourceHelp

*getCellBaseResourceHelp*

---

**Description**

A function to get help about available cellbase resources

**Usage**

```
getCellBaseResourceHelp(object, subcategory)
```

**Arguments**

object	a cellBase class object
subcategory	a character the subcategory to be queried

**Details**

This function retrieves available resources for each generic method like getGene, getRegion, get-protein, etc. It help the user see all possible resources to use with the getGeneric methods

**Value**

character vector of the available resources to that particular subcategory

**Examples**

```
cb <- CellBaseR()
# Get help about what resources are available to the getGene method
getCellBaseResourceHelp(cb, subcategory="gene")
# Get help about what resources are available to the getRegion method
getCellBaseResourceHelp(cb, subcategory="region")
# Get help about what resources are available to the getXref method
getCellBaseResourceHelp(cb, subcategory="id")
```

---

```
getChromosomeInfo,CellBaseR-method  
getChromosomeInfo
```

---

### Description

A method to query sequence data from Cellbase web services.

### Usage

```
## S4 method for signature 'CellBaseR'  
getChromosomeInfo(object, ids, resource, param = NULL)
```

### Arguments

object	an object of class CellBaseR
ids	a character vector of chromosome ids to be queried
resource	a character vector to specify the resource to be queried
param	a object of class CellBaseParam specifying additional param for the query

### Details

A method to query sequence data from Cellbase web services. This method retrieves information about chromosomes, including its size and detailed information about its different cytobands

### Value

a dataframe with the results of the query

### See Also

<https://github.com/opencb/cellbase/wiki> and the RESTful API documentation <http://bioinfo.hpc.cam.ac.uk/cellbase/webservices/>

### Examples

```
cb <- CellBaseR()  
res <- getChromosomeInfo(object=cb, ids="22", resource="info")
```

---

```
getClinical,CellBaseR-method  
    getClinical
```

---

## Description

A method to query Clinical data from Cellbase web services.

## Usage

```
## S4 method for signature 'CellBaseR'  
getClinical(object, param = NULL)
```

## Arguments

object	an object of class CellBaseR
param	a object of class CellBaseParam specifying the parameters limiting the Cell-BaseR

## Details

This method retrieves clinically relevant variants annotations from multiple resources including clinvar, cosmic and gwas catalog. Furthermore, the user can filter these data in many ways including phenotype, genes, rs, etc.,

## Value

a dataframe with the results of the query

## See Also

<https://github.com/opencb/cellbase/wiki> and the RESTful API documentation <http://bioinfo.hpc.cam.ac.uk/cellbase/webservices/>

## Examples

```
cb <- CellBaseR()  
cbParam <- CellBaseParam(gene=c("TP73", "TET1"))  
res <- getClinical(object=cb,param=cbParam)
```

---

`getClinicalByGene`      *getClinicalByGene*

---

**Description**

A convenience method to fetch clinical variants for specific gene/s

**Usage**

```
getClinicalByGene(object, id, param = NULL)
```

**Arguments**

<code>object</code>	an object of <code>CellBaseR</code> class
<code>id</code>	a character vector of HUGO symbol (gene names)
<code>param</code>	an object of class <code>CellBaseParam</code>

**Value**

a dataframe of the query result

**Examples**

```
cb <- CellBaseR()
res <- getClinicalByGene(cb, "TET1")
```

---

`getClinicalByRegion`      *getClinicalByRegion*

---

**Description**

A convenience method to fetch clinical variants for specific region/s

**Usage**

```
getClinicalByRegion(object, id, param = NULL)
```

**Arguments**

<code>object</code>	an object of class <code>CellBaseR</code>
<code>id</code>	a character vector of genomic regions, eg 17:1000000-1100000
<code>param</code>	an object of class <code>CellBaseParam</code>

**Value**

a dataframe of the query result

**Examples**

```
cb <- CellBaseR()
res <- getClinicalByRegion(cb, "17:1000000-1189811")
```

---

```
getConservationByRegion
      getConservationByRegion
```

---

**Description**

A convenience method to fetch conservation data for specific region/s

**Usage**

```
getConservationByRegion(object, id, param = NULL)
```

**Arguments**

object	an object of class CellBaseR
id	a character vector of genomic regions, eg 17:1000000-1100000
param	an object of class CellBaseParam

**Value**

a dataframe of the query result

**Examples**

```
cb <- CellBaseR()
res <- getConservationByRegion(cb, "17:1000000-1189811")
```

---

```
getGene, CellBaseR-method
      getGene
```

---

**Description**

A method to query gene data from Cellbase web services.

**Usage**

```
## S4 method for signature 'CellBaseR'
getGene(object, ids, resource, param = NULL)
```

**Arguments**

object	an object of class CellBaseR
ids	a character vector of gene ids to be queried
resource	a character vector to specify the resource to be queried
param	an object of class CellBaseParam specifying additional param for the CellBaseR

**Details**

This method retrieves various gene annotations including transcripts and exons data as well as gene expression and clinical data

**Value**

a dataframe with the results of the query

**See Also**

<https://github.com/opencb/cellbase/wiki> and the RESTful API documentation <http://bioinfo.hpc.cam.ac.uk/cellbase/webservices/>

**Examples**

```
cb <- CellBaseR()
res <- getGene(object=cb, ids=c("TP73", "TET1"), resource="info")
```

---

getGeneInfo

*getGeneInfo*

---

**Description**

A convenience method to fetch gene annotations specific gene/s

**Usage**

```
getGeneInfo(object, id, param = NULL)
```

**Arguments**

object	an object of class CellBaseR
id	a character vector of HUGO symbol (gene names)
param	an object of class CellBaseParam

**Value**

a dataframe of the query result

**Examples**

```
cb <- CellBaseR()
res <- getGeneInfo(cb, "TET1")
```

---

getMeta,CellBaseR-method  
*getMeta*

---

### Description

A method for getting the available metadata from the cellbase web services

### Usage

```
## S4 method for signature 'CellBaseR'  
getMeta(object, resource)
```

### Arguments

object            an object of class CellBaseR  
resource          the resource you want to query it metadata

### Details

This method is for getting information about the available species and available annotation, assembly for each species from the cellbase web services.

### Value

a dataframe with the results of the query

### See Also

<https://github.com/opencb/cellbase/wiki> and the RESTful API documentation <http://bioinformatics.cam.ac.uk/cellbase/webservices/>

### Examples

```
cb <- CellBaseR()  
res <- getMeta(object=cb, resource="species")
```

---

getProtein,CellBaseR-method  
*getProtein*

---

### Description

A method to query protein data from Cellbase web services.

### Usage

```
## S4 method for signature 'CellBaseR'  
getProtein(object, ids, resource, param = NULL)
```

**Arguments**

object	an object of class CellBaseR
ids	a character vector of uniprot ids to be queried, should be one or more of uniprot ids, for example O15350.
resource	a character vector to specify the resource to be queried
param	a object of class CellBaseParam specifying additional param for the query

**Details**

This method retrieves various protein annotations including protein description, features, sequence, substitution scores, evidence, etc.

**Value**

an object of class CellBaseResponse which holds a dataframe with the results of the query

**Examples**

```
cb <- CellBaseR()
res <- getProtein(object=cb, ids="O15350", resource="info")
```

---

<code>getProteinInfo</code>	<i>getProteinInfo</i>
-----------------------------	-----------------------

---

**Description**

A convenience method to fetch annotations for specific protein/s

**Usage**

```
getProteinInfo(object, id, param = NULL)
```

**Arguments**

object	an object of class CellBaseR
id	a character vector of Uniprot Ids
param	an object of class CellBaseParam

**Value**

a dataframe of the query result

**Examples**

```
cb <- CellBaseR()
res <- getProteinInfo(cb, "O15350")
```



---

getRegion, CellBaseR-method  
*getRegion*

---

## Description

A method to query features within a genomic region from Cellbase web services.

## Usage

```
## S4 method for signature 'CellBaseR'  
getRegion(object, ids, resource, param = NULL)
```

## Arguments

object	an object of class CellBaseR
ids	a character vector of the regions to be queried, for example, "1:1000000-1200000" should always be in the form 'chr:start-end'
resource	a character vector to specify the resource to be queried
param	a object of class CellBaseParam specifying additional param for the query

## Details

This method retrieves various genomic features from a given region including genes, snps, clinically relevant variants, proteins, etc.

## Value

a dataframe with the results of the query

## See Also

<https://github.com/opencb/cellbase/wiki> and the RESTful API documentation <http://bioinfo.hpc.cam.ac.uk/cellbase/webservices/>

## Examples

```
cb <- CellBaseR()  
res <- getRegion(object=cb, ids="17:1000000-1200000", resource="gene")
```

---

```
getRegulatoryByRegion  getRegulatoryByRegion
```

---

**Description**

A convenience method to fetch regulatory data for specific region/s

**Usage**

```
getRegulatoryByRegion(object, id, param = NULL)
```

**Arguments**

object	an object of class CellBaseR
id	a character vector of genomic regions, eg 17:1000000-1100000
param	an object of class CellBaseParam

**Value**

a dataframe of the query result

**Examples**

```
cb <- CellBaseR()
res <- getRegulatoryByRegion(cb, "17:1000000-1189811")
```

---

```
getSnp,CellBaseR-method
      getSnp
```

---

**Description**

A method to query genomic variation data from Cellbase web services.

**Usage**

```
## S4 method for signature 'CellBaseR'
getSnp(object, ids, resource, param = NULL)
```

**Arguments**

object	an object of class CellBaseR
ids	a character vector of the ids to be queried, must be a valid rsid, for example 'rs6025'
resource	a character vector to specify the resource to be queried
param	a object of class CellBaseParam specifying additional param for the query

**Details**

This method retrieves known genomic variants (snps) and their annotations including population frequencies from 1k genomes and Exac projects as well as clinical data and various other annotations

**Value**

a dataframe with the results of the query

**See Also**

<https://github.com/opencb/cellbase/wiki> and the RESTful API documentation <http://bioinfo.hpc.cam.ac.uk/cellbase/webservices/>

**Examples**

```
cb <- CellBaseR()
res <- getSnp(object=cb, ids="rs6025", resource="info")
```

---

getSnpByGene

*getSnpByGene*

---

**Description**

A convenience method to fetch known variants (snps) for specific gene/s

**Usage**

```
getSnpByGene(object, id, param = NULL)
```

**Arguments**

object	an object of class CellBaseR
id	a character vector of HUGO symbol (gene names)
param	an object of class CellBaseParam

**Value**

a dataframe of the query result

**Examples**

```
cb <- CellBaseR()
param <- CellBaseParam(limit = 10)
res <- getSnpByGene(cb, "TET1", param = param)
```

---

```
getTf,CellBaseR-method  
      getTf
```

---

## Description

A method to query transcription factors binding sites data from Cellbase web services.

## Usage

```
## S4 method for signature 'CellBaseR'  
getTf(object, ids, resource, param = NULL)
```

## Arguments

object	an object of class CellBaseR
ids	a character vector of the ids to be queried, must be a valid transcription factor name, for example, eg, CTCF
resource	a character vector to specify the resource to be queried
param	a object of class CellBaseParam specifying additional param for the query

## Details

This method retrieves various transcription factors binding sites data

## Value

a dataframe with the results of the query

## See Also

<https://github.com/openCB/cellbase/wiki> and the RESTful API documentation <http://bioinformatics.cam.ac.uk/cellbase/webservices/>

## Examples

```
cb <- CellBaseR()  
param <- CellBaseParam(limit = 12)  
res <- getTf(object=cb, ids="CTCF", resource="tfbs", param=param)
```

---

```
getTfbsByRegion      getTfbsByRegion
```

---

**Description**

A convenience method to fetch Transcription factors data for specific region/s

**Usage**

```
getTfbsByRegion(object, id, param = NULL)
```

**Arguments**

object	an object of class CellBaseR
id	a character vector of genomic regions, eg 17:1000000-1100000
param	an object of class CellBaseParam

**Value**

a dataframe of the query result

**Examples**

```
cb <- CellBaseR()
res <- getTfbsByRegion(cb, "17:1000000-1189811")
```

---

```
getTranscript, CellBaseR-method
      getTranscript
```

---

**Description**

A method to query transcript data from Cellbase web services.

**Usage**

```
## S4 method for signature 'CellBaseR'
getTranscript(object, ids, resource, param = NULL)
```

**Arguments**

object	an object of class CellBaseR
ids	a character vector of the transcript ids to be queried, use ensemble transcript IDs eg, ENST00000380152
resource	a character vector to specify the resource to be queried
param	an object of class CellBaseParam specifying additional params for the query

**Details**

This method retrieves various genomic annotations for transcripts including exons, cDNA sequence, annotations flags, and cross references, etc.

**Value**

a dataframe with the results of the query

**See Also**

<https://github.com/opencb/cellbase/wiki> and the RESTful API documentation <http://bioinfo.hpc.cam.ac.uk/cellbase/webservices/>

**Examples**

```
cb <- CellBaseR()
res <- getTranscript(object=cb, ids="ENST00000373644", resource="info")
```

---

<code>getTranscriptByGene</code>	<i>getTranscriptByGene</i>
----------------------------------	----------------------------

---

**Description**

A convenience method to fetch transcripts for specific gene/s

**Usage**

```
getTranscriptByGene(object, id, param = NULL)
```

**Arguments**

<code>object</code>	an object of class <code>CellBaseR</code>
<code>id</code>	a character vector of HUGO symbol (gene names)
<code>param</code>	an object of class <code>CellBaseParam</code>

**Value**

a dataframe of the query result

**Examples**

```
cb <- CellBaseR()
res <- getTranscriptByGene(cb, "TET1")
```

---

getVariant, CellBaseR-method  
*getVariant*

---

## Description

A method to query variant annotation data from Cellbase web services from Cellbase web services.

## Usage

```
## S4 method for signature 'CellBaseR'  
getVariant(object, ids, resource, param = NULL)
```

## Arguments

object	an object of class CellBaseR
ids	a character vector of the ids to be queried, must be in the following format 'chr:start:ref:alt', for example, '1:128546:A:T'
resource	a character vector to specify the resource to be queried
param	a object of class CellBaseParam specifying additional param for the query

## Details

This method retrieves extensive genomic annotations for variants including consequence types, conservation data, population frequencies from 1k genomes and Exac projects, etc. as well as clinical data and various other annotations

## Value

a dataframe with the results of the query

## See Also

<https://github.com/opencb/cellbase/wiki> and the RESTful API documentation <http://bioinfo.hpc.cam.ac.uk/cellbase/webservices/>

## Examples

```
cb <- CellBaseR()  
res <- getVariant(object=cb, ids="19:45411941:T:C", resource="annotation")
```

---

```
getVariantAnnotation  getVariantAnnotation
```

---

**Description**

A convenience method to fetch variant annotation for specific variant/s

**Usage**

```
getVariantAnnotation(object, id, param = NULL)
```

**Arguments**

object	an object of class CellBaseR
id	a character vector of length < 200 of genomic variants, eg 19:45411941:T:C
param	an object of class CellBaseParam

**Value**

a dataframe of the query result

**Examples**

```
cb <- CellBaseR()
res <- getVariantAnnotation(cb, "19:45411941:T:C")
```

---

```
getXref,CellBaseR-method
  getXref
```

---

**Description**

A method to query cross reference data from Cellbase web services.

**Usage**

```
## S4 method for signature 'CellBaseR'
getXref(object, ids, resource, param = NULL)
```

**Arguments**

object	an object of class CellBaseR
ids	a character vector of the ids to be queried, any crossreferenceable ID, gene names, transcript ids, uniprot ids, etc.
resource	a character vector to specify the resource to be queried
param	a object of class CellBaseParam specifying additional param for the query



**Details**

This method retrieves cross references for genomic identifiers, eg ENSEMBL ids, it also provide starts\_with service that is useful for autocomplete services.

**Value**

a dataframe with the results of the query

**See Also**

<https://github.com/opencb/cellbase/wiki> and the RESTful API documentation <http://bioinformatics.cam.ac.uk/cellbase/webservices/>

**Examples**

```
cb <- CellBaseR()
res <- getXref(object=cb, ids="ENST00000373644", resource="xref")
```

# Index

AnnotateVcf  
    (AnnotateVcf,CellBaseR-method),  
    3  
AnnotateVcf,CellBaseR-method, 3

CellBaseParam, 4  
CellBaseParam-class, 5  
CellBaseR, 5  
cellbaseR (cellbaseR-package), 2  
CellBaseR-class, 6  
cellbaseR-package, 2  
createGeneModel, 7

GeneRegionTrack, 7  
getCaddScores, 8  
getCellBase  
    (getCellBase,CellBaseR-method),  
    8  
getCellBase,CellBaseR-method, 8  
getCellBaseResourceHelp, 9  
getChromosomeInfo  
    (getChromosomeInfo,CellBaseR-method),  
    10  
getChromosomeInfo,CellBaseR-method, 10  
getClinical  
    (getClinical,CellBaseR-method),  
    11  
getClinical,CellBaseR-method, 11  
getClinicalByGene, 12  
getClinicalByRegion, 12  
getConservationByRegion, 13  
getGene (getGene,CellBaseR-method), 13  
getGene,CellBaseR-method, 13  
getGeneInfo, 14  
getMeta (getMeta,CellBaseR-method), 15  
getMeta,CellBaseR-method, 15  
getProtein  
    (getProtein,CellBaseR-method),  
    15  
getProtein,CellBaseR-method, 15  
getProteinInfo, 16  
getRegion (getRegion,CellBaseR-method),  
    17  
getRegion,CellBaseR-method, 17  
getRegulatoryByRegion, 18  
getSnp (getSnp,CellBaseR-method), 18  
getSnp,CellBaseR-method, 18  
getSnpByGene, 19  
getTf (getTf,CellBaseR-method), 20  
getTf,CellBaseR-method, 20  
getTfbsByRegion, 21  
getTranscript  
    (getTranscript,CellBaseR-method),  
    21  
getTranscript,CellBaseR-method, 21  
getTranscriptByGene, 22  
getVariant  
    (getVariant,CellBaseR-method),  
    23  
getVariant,CellBaseR-method, 23  
getVariantAnnotation, 24  
getXref (getXref,CellBaseR-method), 24  
getXref,CellBaseR-method, 24