

Package ‘contiBAIT’

April 11, 2018

Type Package

Title Improves Early Build Genome Assemblies using Strand-Seq Data

Version 1.6.0

Date 2016-02-02

Author Kieran O'Neill, Mark Hills, Mike Gottlieb

Maintainer Kieran O'Neill <koneill@bccrc.ca>

Description Using strand inheritance data from multiple single cells from the organism whose genome is to be assembled, contiBAIT can cluster unbridged contigs together into putative chromosomes, and order the contigs within those chromosomes.

License BSD_2_clause + file LICENSE

Depends BH (>= 1.51.0-3), Rsamtools (>= 1.21)

LinkingTo Rcpp, BH

Imports grDevices, clue, cluster, gplots, IRanges, GenomicRanges, S4Vectors, Rcpp, TSP, GenomicFiles, gtools, rtracklayer, BiocParallel, DNACopy, colorspace, reshape2, ggplot2, methods, exomeCopy, GenomicAlignments, diagram

Suggests BiocStyle

biocViews CellBasedAssays, QualityControl, WholeGenome, Genetics, GenomeAssembly

Collate 'AllClasses.R' 'AllGenerics.R' 'BAIT.R'
'barplotLinkageGroupCalls.R' 'clusterContigs.R'
'computeConsensus.R' 'computeSim.R' 'contiBAIT.R'
'findSimilarLibraries.R' 'fixLinkageGroups.R'
'highlightAssemblyErrors.R' 'ideogramPlot.R'
'locateMisorients.R' 'makeBoxPlot.R' 'makeChrTable.R'
'mapGapFromOverlap.R' 'mergeFlankedLGs.R'
'orderAllLinkageGroups.R' 'orderContigsGreedy.R'
'orderContigsTSP.R' 'plotContigOrder.R' 'plotLGDistances.R'
'plotWCdistribution.R' 'preprocessStrandTable.R'
'reorientAndMergeLGs.R' 'strandSeqFreqTable.R' 'thoroughBed.R'
'writeBed.R'

RoxygenNote 5.0.1

NeedsCompilation yes

R topics documented:

BAIT	3
barplotLinkageGroupCalls,LinkageGroupList,ChrTable-method	4
ChrTable-class	4
clusterContigs,StrandStateMatrix-method	5
contiBAIT	6
ContigOrdering-class	7
exampleChrTable	8
exampleContigOrder	8
exampleCrickFreq	8
exampleDividedChr	8
exampleLGLList	9
exampleLibList	9
exampleReadCounts	9
exampleStrandFreq	9
exampleWatsonFreq	9
exampleWCMatrix	10
findSimilarLibraries,StrandStateMatrix,StrandReadMatrix,ChrTable-method	10
fixLinkageGroups,ContigOrdering,StrandStateList,LinkageGroupList-method	11
highlightAssemblyErrors	12
ideogramPlot,StrandReadMatrix,StrandReadMatrix,ChrTable-method	13
LibraryGroupList-class	14
LinkageGroupList-class	14
locateMisorients,GRanges-method	15
makeBoxPlot,ChrTable,LinkageGroupList-method	16
makeChrTable	16
mapGapFromOverlap	17
mergeFlankedLGs,LinkageGroupList,StrandStateMatrix-method	18
orderAllLinkageGroups,LinkageGroupList,StrandStateMatrix,StrandFreqMatrix,StrandReadMatrix-method	19
orderContigsGreedy	20
orderContigsTSP	20
OrientationFrame-class	21
plotContigOrder,ContigOrdering-method	22
plotLGDistances,LinkageGroupList,StrandStateMatrix-method	22
plotWCdistribution,StrandFreqMatrix-method	23
preprocessStrandTable,StrandFreqMatrix-method	24
reorientAndMergeLGs,LinkageGroupList,StrandStateMatrix-method	25
show,ContigOrdering-method	26
show,LibraryGroupList-method	26
show,LinkageGroupList-method	27
show,OrientationFrame-method	27
show,StrandFreqMatrix-method	28
show,StrandReadMatrix-method	28
show,StrandStateList-method	29
show,StrandStateMatrix-method	29
StrandFreqMatrix-class	30
StrandReadMatrix-class	30
strandSeqFreqTable	31
StrandStateList-class	32
StrandStateMatrix-class	32

<i>BAIT</i>	3
thoroughBed,ANY,LibraryGroupList-method	33
writeBed,ANY,OrientationFrame,ContigOrdering-method	34
Index	36

BAIT	<i>BAIT – master function to process strand-seq libraries into BAIT ideograms</i>
------	---

Description

BAIT – master function to process strand-seq libraries into BAIT ideograms

Usage

```
BAIT(path = ".", splitBy = 2e+05, readQual = 10, pairedEnd = TRUE,
      plotBy = "lib", plotName = NULL, chroms = "all", verbose = TRUE)
```

Arguments

- path String denoting location of Strand-seq bam files (default is ".")
- splitBy numeric value of binsize for plotting. default is 200000
- readQual Integer dictating the minimal mapping quality required for a read to be accepted. Default is 10.
- pairedEnd Whether the bam files being read are in paired end format. Default is TRUE. Note,
- plotBy Whether to plot by library ('lib') or chromosome ('chr')
- plotName character which determines file name to be saved. Default is to open an R plot from the terminal
- chroms vector of chromosome number to prevent contig plotting. eg for humans use 1:24. Default is 'all'
- verbose prints messages to the terminal (default is TRUE)

Value

ideogram plots

Examples

```
## Not run:

#Not run because this takes a minute or two:
bamPath=file.path(system.file(package='contiBAIT'), 'extdata')

BAIT(bamPath, pairedEnd = FALSE) #our example data is single-end

## End(Not run)
```

```
barplotLinkageGroupCalls,LinkageGroupList,ChrTable-method
```

Bar plot all linkage groups, with the true chromosomes of contigs coloured.

Description

Bar plot all linkage groups, with the true chromosomes of contigs coloured.

Usage

```
## S4 method for signature 'LinkageGroupList,ChrTable'
barplotLinkageGroupCalls(object, chrTable,
  by = "lg", returnTable = FALSE)
```

Arguments

object	LinkageGroupList, as generated by clusterContigs
chrTable	GRanges object containing assembly information about the contigs, including a meta column called 'name' that has names matching the object. Note that the rownames of chrTable should be the contig names, as they are used in object, and the first column (chromosome name) will be used to order by chromosome if 'chr' option used in by parameter. To use a bam file header, the product of makeChrTable(bamFile) is suitable for input
by	whether to plot by linkage group (if 'lg') or chromosomes ('chr')
returnTable	TRUE to return chromosome length matrix. Note to include legend, use legend=rownames(chr.table) for by='lg', and legend=colnames(chr.table) for by='chr'

Value

a matrix of lengths of each chromosome (rows) in each linkage group (columns)

Examples

```
data("exampleLGList")
data("exampleDividedChr")

barplotLinkageGroupCalls(exampleLGList, exampleDividedChr)
```

```
ChrTable-class
```

A class for storing chromosome/fragment lengths

Description

This class is a GRanges object with a meta column called name, which represents the fragment name.

Constructor for ChrTable

Usage

```
ChrTable(chrRanges = GRanges())
```

Arguments

chrRanges a GRanges object with a meta column called name, which represents the fragment name

Value

a ChrTable

clusterContigs,StrandStateMatrix-method

clusterContigs – agglomeratively clusters contigs into linkage groups based on strand inheritance

Description

clusterContigs – agglomeratively clusters contigs into linkage groups based on strand inheritance

Usage

```
## S4 method for signature 'StrandStateMatrix'
clusterContigs(object, similarityCutoff = 0.7,
  recluster = NULL, minimumLibraryOverlap = 5, randomise = TRUE,
  randomSeed = NULL, randomWeight = NULL, clusterParam = NULL,
  clusterBy = "hetero", verbose = TRUE)
```

Arguments

object data.frame containing strand inheritance information for every contig (rows) in every library (columns). This should be the product of strandSeqFreqTable

similarityCutoff place contigs in a cluster when their strand state is at least this similar

recluster Number of times to recluster and take the consensus of. If NULL, clustering is run only once.

minimumLibraryOverlap for two contigs to be clustered together, the strand inheritance must be present for both contigs in at least this many libraries (in addition to their similarity being at least similarityCutoff)

randomise whether to reorder contigs before clustering

randomSeed random seed to initialize clustering

randomWeight vector of weights for contigs for resampling. If NULL, uniform resampling is used. Typically this should be a measure of contig quality, such as library coverage, so that clustering tends to start from the better quality contigs.

clusterParam optional BiocParallelParam specifying cluster to use for parallel execution. When NULL, execution will be serial.

clusterBy	Method for performing clustering. Default is 'hetero' (for comparing heterozygous calls to homozygous). Alternative is 'homo' (for comparison between the two homozygous calls)
verbose	prints function progress

Details

Note that a more stringent similarity cutoff will result in more clusters, and a longer run time, since at every iteration a distance is computed to the existing clusters. However, in lower-quality data, a more stringent cutoff may be necessary to reduce the number of contigs that are erroneously grouped.

Note that clusterParam requires BiocParallel to be installed.

Value

LinkageGroupList of vectors containing labels of contigs belonging to each linkage group

Examples

```
data("exampleWCMatrix")

clusteredContigs <- clusterContigs(exampleWCMatrix, verbose=FALSE)
show(clusteredContigs)
show(clusteredContigs[[1]])
```

contiBAIT	<i>contiBAIT – master function to process strand-seq libraries into ordered linkage groups</i>
-----------	--

Description

contiBAIT – master function to process strand-seq libraries into ordered linkage groups

Usage

```
contiBAIT(path = ".", cluster = 1, clusterParam = NULL,
  saveName = FALSE, filter = FALSE, readQual = 10, readLimit = 10,
  pairedEnd = TRUE, makePlots = FALSE, verbose = TRUE)
```

Arguments

path	String denoting location of Strand-seq bam files (default is ".")
cluster	Integer denoting the number of reclusterings to be performed for creating linkage groups (default is 1)
clusterParam	Number of parallel processors to use when clustering contigs. Default is NULL.
saveName	String denoting the file name for saved data. If FALSE, no intermediate files are saved (default is FALSE)
filter	additional file to split chromosomes based on locations. If this parameter is blank, a filter table will be automatically generated from the header of the first file in bamFileList

readQual	Integer dictating the minimal mapping quality required for a read to be accepted. Default is 10.
readLimit	Minimum number of reads on a contig to make a strand call. Default is 10
pairedEnd	Whether the bam files being read are in paired end format. Default is TRUE. Note, since paired reads will be the same direction, only first mate read of pair is used in output
makePlots	Logical determining whether plots should be created. Default is TRUE
verbose	prints messages to the terminal (default is TRUE)

Value

ordered contigs in bed format. Depending on options, intermediate files and plots will also be generated

Examples

```
#Get a list of BAM files containing libraries for cells from the same organism, aligned to the same genome
#In this case these are the example BAM files provided with the package (hence the call to system.file);
data("exampleDividedChr")
library(BiocParallel)

example.dir <- file.path(system.file(package='contiBAIT'), 'extdata')

orderedContigs <- contiBAIT(path=example.dir,
cluster=1,
clusterParam=MulticoreParam(),
filter=exampleDividedChr,
pairedEnd=FALSE)
```

ContigOrdering-class *A class for storing contig ordering of a linkage group*

Description

This class is a matrix of two character vectors that represent the calculated ordering of a linkage group. The first element of this matrix is the Linkage Group sub-setted by contigs with equal strand states across all libraries in the calculated order. The second element is the names of names of each contig in the calculated order.

Constructor for ContigOrdering

Usage

```
ContigOrdering(ordering = character())
```

Arguments

`ordering` a matrix of two character vectors that represent the calculated ordering of a linkage group. The first element of this matrix is the Linkage Group sub-setted by contigs with equal strand states across all libraries in the calculated order. The second element is the names of names of each contig in the calculated order.

Value

a ContigOrdering

Examples

```
thisOrdering <- ContigOrdering(matrix(ncol=2, c( "LG1.11", "chr2:1000820-2001640",
"LG1.1", "chr2:3002461-4003281")))
```

exampleChrTable	<i>Example of a ChromosomeTable, containing contigs and their lengths</i>
-----------------	---

Description

Example of a ChromosomeTable, containing contigs and their lengths

exampleContigOrder	<i>Example of a ContigOrdering table, containing a list with a matrix of ordered groups element and a StrandStateList element</i>
--------------------	---

Description

Example of a ContigOrdering table, containing a list with a matrix of ordered groups element and a StrandStateList element

exampleCrickFreq	<i>An example Crick strand frequencies extracted from BAMS by strandSeqFreqTable where BAITables=TRUE</i>
------------------	---

Description

An example Crick strand frequencies extracted from BAMS by strandSeqFreqTable where BAITables=TRUE

exampleDividedChr	<i>Example of a divided chromosome, containing contigs and their lengths</i>
-------------------	--

Description

Example of a divided chromosome, containing contigs and their lengths

exampleLGList	<i>Example of a LinkageGroupList output from clusterContigs</i>
---------------	---

Description

Example of a LinkageGroupList output from clusterContigs

exampleLibList	<i>Example of a LibraryGroupList, containing library names</i>
----------------	--

Description

Example of a LibraryGroupList, containing library names

exampleReadCounts	<i>Example of read counts extracted from BAMS by strandSeqFreqTable</i>
-------------------	---

Description

Example of read counts extracted from BAMS by strandSeqFreqTable

exampleStrandFreq	<i>Example of strand frequencies extracted from BAMS by strandSeqFreqTable</i>
-------------------	--

Description

Example of strand frequencies extracted from BAMS by strandSeqFreqTable

exampleWatsonFreq	<i>An example Watson strand frequencies extracted from BAMS by strandSeqFreqTable where BAITables=TRUE</i>
-------------------	--

Description

An example Watson strand frequencies extracted from BAMS by strandSeqFreqTable where BAITables=TRUE

exampleWCMatrix	<i>An example StrandStateMatrix containing WW, CC and WC calls for contigs</i>
-----------------	--

Description

An example StrandStateMatrix containing WW, CC and WC calls for contigs

findSimilarLibraries,StrandStateMatrix,StrandReadMatrix,ChrTable-method	<i>findSimilarLibraries – function to identify libraries that hare similar WC patterns on chromosomes</i>
---	---

Description

findSimilarLibraries – function to identify libraries that hare similar WC patterns on chromosomes

Usage

```
## S4 method for signature 'StrandStateMatrix,StrandReadMatrix,ChrTable'
findSimilarLibraries(strandStateMatrix,
  strandReadMatrix, chrGrange, chrNum, cluster = 1, clusterParam = NULL,
  verbose = TRUE)
```

Arguments

strandStateMatrix	A strandStateMatrix object for all libraries across split fragments, derived from preprocessStrandTable
strandReadMatrix	The number of reads present for each strandStateMatrix element. An object of type strandReadMatrix from strandSeqFreqTable
chrGrange	File of type ChrTable (a GRanges object with a meta column titled 'name' determining contig name) to split chromosomes based on locations. name meta should match the rownames of strandStateMatrix and strandReadMatrix
chrNum	The chromosome number to analyse
cluster	Number of times to recluster and take the consensus of. If NULL, clustering is run only once
clusterParam	optional BiocParallelParam specifying cluster to use for parallel execution. When NULL, execution will be serial.
verbose	prints messages to the terminal (default is TRUE)

Value

a list of type LinkageGroupList with two elements; libraries that are mostly Watson, and those that are mostly Crick

Examples

```
#Get a list of BAM files containing libraries for cells from the same organism, aligned to the same genome
#In this case these are the example BAM files provided with the package (hence the call to system.file);
data("exampleDividedChr")
data("exampleWCMatrix")
data("exampleReadCounts")

library(BiocParallel)

example.dir <- file.path(system.file(package='contibAIT'), 'extdata')

chrGrange <- exampleDividedChr[which(exampleDividedChr$name %in% rownames(exampleWCMatrix))]

exampleLibList <- lapply(seq_len(length(unique(seqnames(chrGrange)))), function(x) findSimilarLibraries(exa
exampleLibList <- exampleLibList[!sapply(exampleLibList, is.null)]
exampleLibList <- LibraryGroupList(exampleLibList)

show(exampleLibList)
```

```
fixLinkageGroups,ContigOrdering,StrandStateList,LinkageGroupList-method
fixLinkageGroups – searches for discrepancies within ordered contigs
to highlight erroneously merged fragments.
```

Description

fixLinkageGroups – searches for discrepancies within ordered contigs to highlight erroneously merged fragments.

Usage

```
## S4 method for signature 'ContigOrdering,StrandStateList,LinkageGroupList'
fixLinkageGroups(contigOrdering,
  orderFrame, linkageGroupList, whichLG = NULL, relatedCutOff = 0.6,
  verbose = TRUE)
```

Arguments

contigOrdering	a data.frame of ordered contigs with linkage group names of class ContigOrdering
orderFrame	a list of StrandStateMatrix elements of class StrandStateList
linkageGroupList	List of vectors containing names of contigs belonging to each LG of type LinkageGroupList.
whichLG	vector of integers specifying the element(s) of linkageGroupList to be ordered (i.e. which specific linkage groups to try to order). Default is all LGs.
relatedCutOff	The minimal dissimilarity between adjacent contigs to subset a linkage group into multiple smaller groups. Default is 0.6
verbose	Outputs information to the terminal. Default is TRUE.

Value

a LinkageGroupList with erroneously clustered contigs separated into their own groups

highlightAssemblyErrors

highlightAssemblyErrors – Master function to identify misorientations and chimeras in the assembly

Description

highlightAssemblyErrors – Master function to identify misorientations and chimeras in the assembly

Usage

```
highlightAssemblyErrors(path, splitBy = 1e+06, cluster = 1,
  clusterParam = NULL, pairedEnd = TRUE, qual = 10, gapFile = NULL,
  writeBed = NULL, verbose = TRUE)
```

Arguments

path	String denoting location of Strand-seq bam files
splitBy	integer determining the average size contigs should be split by
cluster	Number of times to recluster and take the consensus of. If NULL, clustering is run only once.
clusterParam	optional BiocParallelParam specifying cluster to use for parallel execution. When NULL, execution will be serial.
pairedEnd	Whether the bam files being read are in paired end format. Default is TRUE. Note,
qual	Mapping quality threshold. Default is 1
gapFile	A GRanges object consisting of start and end locations of assembly gaps (default is NULL)
writeBed	Character vector, this option will write the resulting bed file to a specified location with the character as the file name. Default is NULL
verbose	prints messages to the terminal (default is TRUE)

Value

a directional ChrTable object that can be used in downstream functions (strandSeqFreqTable)

```
ideogramPlot,StrandReadMatrix,StrandReadMatrix,ChrTable-method
      ideogramPlot – plots BAIT-like ideograms
```

Description

ideogramPlot – plots BAIT-like ideograms

Usage

```
## S4 method for signature 'StrandReadMatrix,StrandReadMatrix,ChrTable'
ideogramPlot(WatsonFreqList,
             CrickFreqList, chrTable, plotBy = "lib", showPage = NULL,
             orderFrame = NULL, orientationData = NULL, verbose = TRUE)
```

Arguments

WatsonFreqList	data.frame of Watson calls. Product of strandSeqFreqTable[[3]] when BAITtables=TRUE
CrickFreqList	data.frame of Crick calls. Product of strandSeqFreqTable[[4]] when BAITtables=TRUE
chrTable	A data.frame consisting of chromosomes and lengths. Generated by makeChrTable(). Note rownames equal to chromosome names are required
plotBy	Whether to generate a plot for each library ('lib') or a plot for each chromosome ('chr')
showPage	Integer specifying which LG (if plotBy='chr') or libraries (if plotBy='lib') to plot. Useful when not plotting to a file, or when wishing to subset data. Default is NULL
orderFrame	ordered data.frame of contigs (produced by orderAllLinkageGroups). Default is FALSE, where plots will be made from elements in chrTable.
orientationData	data.frame of contig orientations of type OrientationFrame telling which reads to flip Watson and Crick counts
verbose	prints messages to the terminal (default is TRUE)

Value

ordered contigs in bed format. Depending on options, intermediate files and plots will also be generated

Examples

```
data("exampleWatsonFreq")
data("exampleCrickFreq")
data('exampleDividedChr')

singleWatsonLibrary <- StrandReadMatrix(exampleWatsonFreq[,2, drop=FALSE])
singleCrickLibrary <- StrandReadMatrix(exampleCrickFreq[,2, drop=FALSE])

ideogramPlot(singleWatsonLibrary, singleCrickLibrary, exampleDividedChr)
```

 LibraryGroupList-class

A class for storing library group calls for contigs

Description

This class is a list of lists, each primary list element is a chromosome/contig, and contains 2 sub-list elements: a list of "Mostly Watson" and "Mostly Crick" library names.

Constructor forLibraryGroupList

Usage

```
LibraryGroupList(libraryGroups = list(), names = character())
```

Arguments

`libraryGroups` a list of lists, with each primary list element representing a chromosome with two internal list elements; a character vector of mostly watson library names, and a character vector of mostly Crick library names

`names` a vector of names of linkage groups

Value

a LibraryGroupList

Examples

```
lg1 <- LinkageGroupList(list(a=c('library1', 'library2'), b=c('library3')), names=c('chr1_Mostly_Crick', 'chr1_Mostly_Watson'))
lg2 <- LinkageGroupList(list(a=c('library1'), b=c('library6', 'library4')), names=c('chr2_Mostly_Crick', 'chr2_Mostly_Watson'))
libList <- LibraryGroupList(list(lg1, lg2))
```

 LinkageGroupList-class

A class for storing linkage group calls for contigs

Description

This class is simply a list of character strings containing the names of linkage groups.

Constructor forLinkageGroupList

Usage

```
LinkageGroupList(linkageGroups = list(), names = character())
```

Arguments

`linkageGroups` a list of character vectors of names of contigs in each LG

`names` a vector of names of linkage groups

Value

a LinkageGroupList

Examples

```
lgList <- LinkageGroupList(list(lg1=c('contig1', 'contig2'), lg2=c('contig3')),
names=c('lg1', 'lg20'))
```

locateMisorients, GRanges-method

locateMisorients – function to identify libraries that hare similar WC patterns on chromosomes

Description

locateMisorients – function to identify libraries that hare similar WC patterns on chromosomes

Usage

```
## S4 method for signature 'GRanges'
locateMisorients(compiledGrange, gapFile = NULL,
stateNum = 3, readCutOff = 40, writeBed = NULL, verbose = TRUE)
```

Arguments

compiledGrange	A GRanges object consisting of read locations. Can be an individual file or the product of thoroughBed
gapFile	A GRanges object consisting of start and end locations of assembly gaps (default is NULL)
stateNum	The number of expected strand states. Default is 3 (WW, WC and CC). Function may exhibit unusual behaviour is changed
readCutOff	The minimal number of reads required to make an accurate strand state call. Default is 40.
writeBed	Character vector, this option will write the resulting bed file to a specified location with the character as the file name. Defulat is NULL
verbose	prints messages to the terminal (default is TRUE)

Value

a directional ChrTable object that can be used in downstream functions (strandSeqFreqTable)

```
makeBoxPlot,ChrTable,LinkageGroupList-method
```

makeBoxPlot – creates boxplot of contigs included in the analysis vs those excluded

Description

makeBoxPlot – creates boxplot of contigs included in the analysis vs those excluded

Usage

```
## S4 method for signature 'ChrTable,LinkageGroupList'
makeBoxPlot(chrTable, linkage.contigs)
```

Arguments

chrTable A GRanges object consisting of contigs and positions. A meta column called 'names' must be present with names in the same format as those from linkage.contigs. Generated by makeChrTable().

linkage.contigs A list of clustered contigs, generated by clusterContigs()

Value

a box plot of included and excluded contigs

Examples

```
#make an example barplot of data

data("exampleLGList")
data("exampleChrTable")
makeBoxPlot(exampleChrTable, exampleLGList)
```

```
makeChrTable
```

makeChrTable – Pulls out chromosome and length data from the header of a bam file

Description

makeChrTable – Pulls out chromosome and length data from the header of a bam file

Usage

```
makeChrTable(bamFile, splitFile = NULL, splitBy = NULL, verbose = TRUE)
```


Arguments

bamFile	string of location of a bam file to extract header data from
splitFile	GRanges object (of type chr, start and end: no strand or meta columns) of locations in which to split the assembly, such as previously determined locations of contig chimerism
splitBy	integer determining the average size contigs should be split by
verbose	if FALSE, no messages appear on terminal

Details

makeChrTable creates a table with chromosome name and chromosome length by extracting header data from the supplied bam file.

Value

a GRanges object of class ChrTable, containing information on the organism's chromosomes as extracted from the BAM file header.

Examples

```
#Get an example BAM file and generate a chromosome table featuring fragment names and lengths
example.bam <- list.files(file.path(system.file(package='contibAIT'), 'extdata'), full.names=TRUE)[1]

chrTable <- makeChrTable(example.bam)

show(chrTable)

dividedChr <- makeChrTable(example.bam, splitBy=1000000)

show(dividedChr)
```

mapGapFromOverlap	<i>mapGapFromOverlap – function to co-localize strand state changes with assembly gaps</i>
-------------------	--

Description

mapGapFromOverlap – function to co-localize strand state changes with assembly gaps

Usage

```
mapGapFromOverlap(sceFile, gapFile, chrTable, verbose = TRUE,
  overlapNum = 4)
```

Arguments

sceFile	GRanges object of strand state change locations in BED format
gapFile	GRanges object of assembly gaps in BED format (can be downloaded from UCSC table browser)
chrTable	GRanges object of chromosome table (product of makeChrTable)
verbose	prints messages to the terminal (default is TRUE)
overlapNum	Minimal number of strand state changes that overlap with a gap before assembly is cut at that location

Value

a GRanges object of all contigs split by regions where the sceFile and gapFile GRanges objects overlap.

`mergeFlankedLGs,LinkageGroupList,StrandStateMatrix-method`

mergeFlankedLGs – searches for similarities at the ends of ordered linkage groups to chain groups together

Description

`mergeFlankedLGs` – searches for similarities at the ends of ordered linkage groups to chain groups together

Usage

```
## S4 method for signature 'LinkageGroupList,StrandStateMatrix'
mergeFlankedLGs(linkageGroupList,
  strandStateMatrix, buildConsensus = 1, cluster = NULL,
  clusterParam = NULL, verbose = TRUE)
```

Arguments

<code>linkageGroupList</code>	List of ordered vectors containing names of contigs belonging to each LG, of type <code>LinkageGroupList</code>
<code>strandStateMatrix</code>	Table of type <code>strandStateMatrix</code> encompassing strand state for all contigs. Product of <code>StrandSeqFreqTable</code> .
<code>buildConsensus</code>	number of contigs to take at the end of the linkage group to build a consensus strand state. Default is 5
<code>cluster</code>	Number of times to recluster and take the consensus of. If <code>NULL</code> , clustering is run only once.
<code>clusterParam</code>	optional <code>BiocParallelParam</code> specifying cluster to use for parallel execution. When <code>NULL</code> , execution will be serial.
<code>verbose</code>	Outputs information to the terminal. Default is <code>TRUE</code> .

Value

a list containing a revised LinkageGroupList with merged groups, if appropriate, and a StrandStateMatrix with contigs reoriented, if newly merged groups were in opposite orientations.

orderAllLinkageGroups,LinkageGroupList,StrandStateMatrix,StrandFreqMatrix,StrandReadMatrix-method
Function to call contig ordering algorithms iteratively across each linkage group element

Description

Function to call contig ordering algorithms iteratively across each linkage group element

Usage

```
## S4 method for signature
## 'LinkageGroupList,StrandStateMatrix,StrandFreqMatrix,StrandReadMatrix'
orderAllLinkageGroups(linkageGroupList,
  strandStateMatrix, strandFreqMatrix, strandReadCount, whichLG = NULL,
  saveOrdered = NULL, orderCall = "greedy", randomAttempts = 75,
  verbose = TRUE)
```

Arguments

linkageGroupList	list of vectors, each specifying which contigs belong in which linkage group (product of clusterContigs)
strandStateMatrix	table of strand calls for all contigs (product of preprocessStrandTable)
strandFreqMatrix	table of W:C read proportions (used for QC) (product of strandSeqFreqTable[[1]])
strandReadCount	table of read counts (product of strandSeqFreqTable[[2]])
whichLG	vector of integers specifying the element(s) of linkageGroupList to be ordered (i.e. which specific linkage groups to try to order). Default is all LGs.
saveOrdered	Will return a pdf of heatmaps for each linkage group; String entered becomes the fileName (default is saveOrderedPDF=FALSE)
orderCall	currently either 'greedy' for greedy algorithm or 'TSP' for travelling salesperson algorithm (default is 'greedy')
randomAttempts	integer specifying number of randomized clusterings to identify the best ordering. Default is 75
verbose	Prints messages to the terminal. Default is TRUE

Value

a data.frame of ordered contigs with linkage group names

Examples

```
#Get a data.frame of ordered contigs from cells from the same organism, aligned to the same genome

data("exampleLGList")
data("exampleWCMatrix")
data("exampleStrandFreq")
data("exampleReadCounts")
contigOrder <- orderAllLinkageGroups(exampleLGList, exampleWCMatrix, exampleStrandFreq, exampleReadCounts)

show(contigOrder)
```

orderContigsGreedy	<i>Function to order contigs within a single linkage group using a greedy algorithms Attempt to order contigs within</i>
--------------------	--

Description

Function to order contigs within a single linkage group using a greedy algorithms Attempt to order contigs within

Usage

```
orderContigsGreedy(linkageGroupReadTable, randomAttempts = 75,
  verbose = TRUE)
```

Arguments

linkageGroupReadTable	dataframe of strand calls (product of combineZeroDists or preprocessStrandTable)
randomAttempts	number of times to repeat the greedy algorithm with a random restart
verbose	whether to print verbose messages

Value

list of two members: 1) contig names in order, 2) the original data.frame entered into function correctly ordered

orderContigsTSP	<i>Attempt to order contigs within linkage groups using travelling salesperson algorithm</i>
-----------------	--

Description

Attempt to order contigs within linkage groups using travelling salesperson algorithm

Usage

```
orderContigsTSP(linkageGroupReadTable)
```

Arguments

linkageGroupReadTable
dataframe of strand calls (product of combineZeroDists or preprocessStrandTable)

Value

list of two members: 1) contig names in order, 2) the original data.frame entered into function correctly ordered

OrientationFrame-class

A class for storing contig orientations

Description

This class is a matrix of two character vectors that represent the orientation of contigs. The first element of thismatrix is the contigs name The second element is the orinetation (as either + or -).

Constructor for OrientationFrame

Usage

```
OrientationFrame(orientation = character())
```

Arguments

orientation a matrix of two character vectors that represent the orientation of contigs. The first element of thismatrix is the contigs name The second element is the orinetation (as either + or -).

Value

a OrientationFrame

Examples

```
OrientationFrame(matrix(ncol=2, c("chr4:3002423-4003230", "+",  
"chr4:140113083-141113889", "+")))
```

plotContigOrder,ContigOrdering-method

Plot ordering of contigs within a single linkage group.

Description

Plot ordering of contigs within a single linkage group.

Usage

```
## S4 method for signature 'ContigOrdering'
plotContigOrder(contigOrder, lg = "all",
  verbose = TRUE)
```

Arguments

contigOrder	matrix from orderAllContigs with the subdivided linkage groups and the names of the contigs to plot
lg	Integer specifying the linkage group by which to plot. Default is all
verbose	prints messages to the terminal (default is TRUE)

Value

A ggplot object (which will be plotted automatically if not assigned).

Examples

```
#Get a data.frame of ordered contigs from cells from the same organism, aligned to the same genome
data("exampleContigOrder")

plotContigOrder(exampleContigOrder[[1]], lg=1)
```

plotLGDistances,LinkageGroupList,StrandStateMatrix-method

plotLGDistances – plots a heatmap of the distances between linkage groups

Description

plotLGDistances – plots a heatmap of the distances between linkage groups

Usage

```
## S4 method for signature 'LinkageGroupList,StrandStateMatrix'
plotLGDistances(object,
  allStrands, lg = "all", labels = TRUE, alreadyOrdered = FALSE)
```

Arguments

object	LinkageGroupList
allStrands	StrandStateMatrix for all linkageGroups (usually reoriented by reorientStrandTable)
lg	= 'all' vector of integers to determine which linkage group(s) to plot. 'all' will calculate consensus strand calls for all linkage groups and plot them side by side (default is 'all')
labels	=TRUE if TRUE, contig names will be plotted on the axes
alreadyOrdered	if TRUE, the function will assume that the linkageGroupList is already ordered and not create a dendrogram. Default is FALSE
...	additional parameters to pass to heatmap.2

Value

a heatmap of linkage group calls

Examples

```
data("exampleLGList")
data("exampleWCMatrix")

plotLGDistances(exampleLGList, exampleWCMatrix)
plotLGDistances(exampleLGList, exampleWCMatrix, lg=1)
```

plotWCdistribution,StrandFreqMatrix-method

Creates median distribution boxplots across all libraries and contigs

Description

Creates median distribution boxplots across all libraries and contigs

Usage

```
## S4 method for signature 'StrandFreqMatrix'
plotWCdistribution(object, filterThreshold = 0.8)
```

Arguments

object	object of class StrandFreqMatrix (product of strandSeqFreqTable)
filterThreshold	numeric value used in assessing the threshold for homozygous strand calls. Default is 0.8.

Value

nothing, just plots.

Examples

```
data("exampleStrandFreq")

plotWCdistribution(exampleStrandFreq, filterThreshold=0.8)
```

```
preprocessStrandTable,StrandFreqMatrix-method
```

preprocessStrandTable – remove low quality libraries and contigs before attempting to build a genome

Description

preprocessStrandTable – remove low quality libraries and contigs before attempting to build a genome

Usage

```
## S4 method for signature 'StrandFreqMatrix'
preprocessStrandTable(strandTable,
  strandTableThreshold = 0.8, filterThreshold = 0.8,
  orderMethod = "libsAndConc", lowQualThreshold = 0.9, verbose = TRUE,
  minLib = 10)
```

Arguments

strandTable	data.frame containing the strand table to use as input
strandTableThreshold	threshold at which to call a contig WW or CC rather than WC
filterThreshold	maximum number of libraries a contig can be NA or WC in
orderMethod	the method to order contigs. currently libsAndConc only option. Set to FALSE to not order contigs based on library quality
lowQualThreshold	background threshold at which to toss an entire library. If NULL, function will not make an overall assessment of library quality. Very chimeric assemblies can appear low quality across all libraries.
verbose	messages written to terminal
minLib	minimum number of libraries a contig must be present in to be included in the output

Value

A list of one matrix and three quality data.frames – 1: a matrix of WW/WC/WW calls for all contigs; 3: the quality of libraries used (based on frequencies outside expected ranges); 4: A data.frame of libraries that are of low quality and therefore excluded from analysis; 5: contigs that are present as WC in more libraries than expected. These are excluded from the strandStateMatrix, but are potentially worth investigating for chimerism.

Examples

```
data("exampleStrandFreq")

strandStates <- preprocessStrandTable(exampleStrandFreq, lowQualThreshold=0.8)

show(strandStates[[1]]) # WW-WC-CC matrix
```

```
reorientAndMergeLGs,LinkageGroupList,StrandStateMatrix-method
    reorientAndMergeLGs uses a simple dissimilarity to find misoriented
    fragments within linkage groups.
```

Description

reorientAndMergeLGs uses a simple dissimilarity to find misoriented fragments within linkage groups.

Usage

```
## S4 method for signature 'LinkageGroupList,StrandStateMatrix'
reorientAndMergeLGs(object,
  allStrands, cluster = NULL, clusterParam = NULL, similarityCutoff = 0.9,
  verbose = TRUE)
```

Arguments

object	List of vectors containing names of contigs belonging to each LG.
allStrands	Table of type strandStateMatrix encompassing strand state for all contigs. Product of StrandSeqFreqTable.
cluster	Number of times to recluster and take the consensus of. If NULL, clustering is run only once.
clusterParam	optional BiocParallelParam specifying cluster to use for parallel execution. When NULL, execution will be serial.
similarityCutoff	merge contigs that are more similar this this
verbose	Outputs information to the terminal. Default is TRUE.

Value

a list consisting of a strandStateMatrix (a reoriented version of allStrands), a data.frame of type OrientationFrame containing contig names and orientations, as '+' or '-' and a merged LinkageGroupList.

Examples

```
data(exampleLGList)
data(exampleWCMatrix)

reorientedMatrix <- reorientAndMergeLGs(exampleLGList,
  exampleWCMatrix)

# Note that in this example data, everything is correctly oriented to
# to begin with, so all contigs come out as + orientation
```

show,ContigOrdering-method

show-methods

Description

Shows a ContigOrdering

Usage

```
## S4 method for signature 'ContigOrdering'  
show(object)
```

Arguments

object a ContigOrdering

Value

nothing

show,LibraryGroupList-method

show-methods

Description

Shows a LibraryGroupList

Usage

```
## S4 method for signature 'LibraryGroupList'  
show(object)
```

Arguments

object a LibraryGroupList

Value

nothing

show,LinkageGroupList-method
show-methods

Description

Shows a LinkageGroupList

Usage

```
## S4 method for signature 'LinkageGroupList'  
show(object)
```

Arguments

object a LinkageGroupList

Value

nothing

show,OrientationFrame-method
show-methods

Description

Shows a OrientationFrame

Usage

```
## S4 method for signature 'OrientationFrame'  
show(object)
```

Arguments

object a OrientationFrame

Value

nothing

show,StrandFreqMatrix-method
show-methods

Description

Shows a StrandFreqMatrix

Usage

```
## S4 method for signature 'StrandFreqMatrix'  
show(object)
```

Arguments

object a StrandFreqMatrix

Value

nothing

show,StrandReadMatrix-method
show-methods

Description

Shows a StrandReadMatrix

Usage

```
## S4 method for signature 'StrandReadMatrix'  
show(object)
```

Arguments

object a StrandReadMatrix

Value

nothing

show,StrandStateList-method
show-methods

Description

Shows a StrandStateList

Usage

```
## S4 method for signature 'StrandStateList'  
show(object)
```

Arguments

object a StrandStateList

Value

nothing

show,StrandStateMatrix-method
show-methods

Description

Shows a StrandStateMatrix

Usage

```
## S4 method for signature 'StrandStateMatrix'  
show(object)
```

Arguments

object a StrandStateMatrix

Value

nothing

StrandFreqMatrix-class

A class for storing a matrix of frequencies of Watson to Crick reads for a set of contigs over several libraries

Description

The strand information stored in this object is the ratio of Watson to Crick reads mapping to each contig in each library (cell). This should fall within the range (-1,1). This class simply extends matrix, but with additional validity checking.

Constructor for StrandFreqMatrix

Usage

```
StrandFreqMatrix(counts = matrix(double()))
```

Arguments

counts a double matrix of read count ratios

Value

a StrandFreqMatrix

Examples

```
data("exampleWatsonFreq")
data("exampleCrickFreq")
frequencyMatrix <- sapply(1:ncol(exampleCrickFreq),
function(colNum){exampleCrickFreq[,colNum] / exampleWatsonFreq[,colNum]})

StrandFreqMatrix(frequencyMatrix)
```

StrandReadMatrix-class

A class for storing read counts for a set of contigs over several libraries

Description

The information stored in this class is simple read counts, so should be integers ≥ 0 .

Constructor for StrandReadMatrix

Usage

```
StrandReadMatrix(counts = matrix(integer()))
```

Arguments

counts an integer matrix of read counts

Value

a StrandReadMatrix

Examples

```
data("exampleWatsonFreq")
StrandReadMatrix(exampleWatsonFreq[,2, drop=FALSE])
```

strandSeqFreqTable *strandSeqFreqTable – function to process bam files for contiBAIT*

Description

strandSeqFreqTable – function to process bam files for contiBAIT

Usage

```
strandSeqFreqTable(bamFileList, fieldSep = ".", field = 1, qual = 0,
  rmdup = TRUE, verbose = TRUE, filter = NULL, tileChunk = 1e+05,
  pairedEnd = TRUE, BAITtables = FALSE)
```

Arguments

bamFileList	vector containing the location of the bams file to be read
fieldSep	The field separator of the bam file to use to define the field. Default is '.'
field	The field of the bam file name to use as an index (default is 1)
qual	Mapping quality threshold. Default is 0
rmdup	remove duplicates in output file. Default is TRUE
verbose	prints messages to the terminal (default is TRUE)
filter	additional file of type GRanges (with a meta column titled 'name' determining contig name) to split chromosomes based on locations. If this parameter is blank, a filter table will be automatically generated from the header of the first file in bamFileList.
tileChunk	Number of reads to split bam files into (smaller number requires less RAM). Default is 100000.
pairedEnd	Whether the bam files being read are in paired end format. Default is TRUE. Note, since paired reads will be the same direction, only first mate read of pair is used in output
BAITtables	creates additional matrices in the returned list with just Watson and Crick read counts to be used in downstream BAIT plotting. Default is FALSE

Value

a list containing two matrices: a StrandFreqMatrix of W:C read frequencies, and a StrandReadMatrix of read counts

Examples

```
#Get a list of BAM files containing libraries for cells from the same organism, aligned to the same genome
#In this case these are the example BAM files provided with the package (hence the call to system.file);

example.dir <- file.path(system.file(package='contiBAIT'), 'extdata')
bam.files <- dir(example.dir, full.names=TRUE)

strand.freq <- strandSeqFreqTable(bam.files, pairedEnd = FALSE)

show(strand.freq[[1]])
show(strand.freq[[2]])
```

StrandStateList-class *A class for storing StrandStateList lists for contigs*

Description

This class is a list of StrandStateMatrices, each a subset of the StrandStateMatrix split by linkagegroups

Constructor StrandStateList

Usage

```
StrandStateList(strandGroupList = list(), names = character())
```

Arguments

strandGroupList
a list of StrandStateMatrix elements, with each primary element representing a StrandStateMatrix containing ordered contigs from a LinkageGroupList element

names
a vector of names of StrandStateMatrix elements

Value

a StrandStateList

StrandStateMatrix-class

A class for storing a data frame of discrete strand states of a set of contigs over several libraries

Description

The strand information stored in this object is a call of the strand state of each contig in each library. mapping to each contig in each library (cell). This should fall within the range (-1,1). This class simply extends matrix, but with additional validity checking.

Constructor for StrandStateMatrix

Usage

```
StrandStateMatrix(states = matrix(integer()))
```

Arguments

states an integer matrix of strand states by library

Value

a StrandStateMatrix

Examples

```
StrandStateMatrix(matrix(ncol=2, c(1,3,1,2)))
```

thoroughBed, ANY, LibraryGroupList-method

thoroughBed – function to merge chromosomes from libraries that have the same strand states

Description

thoroughBed – function to merge chromosomes from libraries that have the same strand states

Usage

```
## S4 method for signature 'ANY,LibraryGroupList'
thoroughBed(bamFileList, relatedLibList,
  qual = 10, pairedEnd = TRUE, verbose = TRUE)
```

Arguments

bamFileList vector containing the location of the bams file to be read

relatedLibList list where each element contains all library names that show similar strand pattern. The product of findSimilarLibraries

qual Mapping quality threshold. Default is 10

pairedEnd Whether the bam files being read are in paired end format. Default is TRUE. Note, since paired reads will be the same direction, only first mate read of pair is used in output to reduce file size

verbose prints messages to the terminal (default is TRUE)

Value

a GRanges object comprising merged directional reads from all libraries in relatedLibList.

Examples

```
#Get a list of BAM files containing libraries for cells from the same organism, aligned to the same genome
#In this case these are the example BAM files provided with the package (hence the call to system.file);
data("exampleLibList")
```

```
library(BiocParallel)
```

```
example.dir <- file.path(system.file(package='contibAIT'), 'extdata')
```

```
exampleRange <- thoroughBed(example.dir, exampleLibList)
```

```
show(exampleRange)
```

```
writeBed,ANY,OrientationFrame,ContigOrdering-method
      function to write contig order to BED file
```

Description

function to write contig order to BED file

Usage

```
## S4 method for signature 'ANY,OrientationFrame,ContigOrdering'
writeBed(chrTable,
         orientationData, contigOrder, libWeight = NULL,
         file = "contibAIT_assembly.bed")
```

Arguments

chrTable	a GRanges object with a 'name' meta column matching contig names. Product of makeChrTable
orientationData	data.frame of contig and strand (with rownames matching contig names). Product of reorientAndMergeLGs[[2]]
contigOrder	an object of type ContigOrdering with ordered Linkage Groups and contigs. Product of orderAllLinkageGroups
libWeight	average quality across all libraries for a contig
file	character string for bed file name to write

Value

NULL; BED file written to file

Examples

```
## Not run:  
  
data("exampleDividedChr")  
  
writeBed(exampleDividedChr,  
         reorientedMatrix[[2]],  
         contigOrder)  
  
## End(Not run)
```

Index

*Topic **data**

exampleChrTable, 8
 exampleContigOrder, 8
 exampleCrickFreq, 8
 exampleDividedChr, 8
 exampleLGList, 9
 exampleLibList, 9
 exampleReadCounts, 9
 exampleStrandFreq, 9
 exampleWatsonFreq, 9
 exampleWCMatrix, 10

BAIT, 3

barplotLinkageGroupCalls

(barplotLinkageGroupCalls, LinkageGroupList, ChrTable-method),

4

barplotLinkageGroupCalls, LinkageGroupList, ChrTable-method,

4

barplotLinkageGroupCalls, LinkageGroupList, LinkageGroupList-method, ChrTable, ChrTable-method

(barplotLinkageGroupCalls, LinkageGroupList, ChrTable-method),

4

ChrTable (ChrTable-class), 4

ChrTable-class, 4

clusterContigs

(clusterContigs, StrandStateMatrix-method),

5

clusterContigs, StrandStateMatrix, StrandStateMatrix-method

(clusterContigs, StrandStateMatrix-method),

5

clusterContigs, StrandStateMatrix-method,

5

contIBAIT, 6

ContigOrdering (ContigOrdering-class), 7

ContigOrdering-class, 7

exampleChrTable, 8

exampleContigOrder, 8

exampleCrickFreq, 8

exampleDividedChr, 8

exampleLGList, 9

exampleLibList, 9

exampleReadCounts, 9

exampleStrandFreq, 9

exampleWatsonFreq, 9

exampleWCMatrix, 10

findSimilarLibraries

(findSimilarLibraries, StrandStateMatrix, StrandR

10

findSimilarLibraries, findSimilarLibraries-StrandStateMa

(findSimilarLibraries, StrandStateMatrix, StrandR

10

findSimilarLibraries, StrandStateMatrix, StrandReadMatrix

10

fixLinkageGroups

(fixLinkageGroups, ContigOrdering, StrandStateList

11

fixLinkageGroups, ContigOrdering, StrandStateList, Linkage

11

fixLinkageGroups-ContigOrdering-StrandStateList-method

(fixLinkageGroups, ContigOrdering, StrandStateList

11

highlightAssemblyErrors, 12

highlightAssemblyErrors, highlightAssemblyErrors-GRanges

(highlightAssemblyErrors), 12

ideogramPlot

(ideogramPlot, StrandReadMatrix, StrandReadMatrix

13

ideogramPlot, StrandReadMatrix, StrandReadMatrix, ChrTable

13

ideogramPlot, StrandReadMatrix, StrandReadMatrix-method, C

(ideogramPlot, StrandReadMatrix, StrandReadMatrix

13

LibraryGroupList

(LibraryGroupList-class), 14

LibraryGroupList-class, 14

LinkageGroupList

(LinkageGroupList-class), 14

LinkageGroupList-class, 14

locateMisorientations

(locateMisorientations, GRanges-method),

15

locateMisorientations, GRanges-method, 15

- locateMisorientations, locateMisorientations-GRanges-method, (locateMisorientations, GRanges-method), 15
- makeBoxPlot (makeBoxPlot, ChrTable, LinkageGroupList-method), 16
- makeBoxPlot, ChrTable, LinkageGroupList-method, 16
- makeBoxPlot-ChrTable-LinkageGroupList-method (makeBoxPlot, ChrTable, LinkageGroupList-method), 16
- makeChrTable, 16
- mapGapFromOverlap, 17
- mergeFlankedLGs (mergeFlankedLGs, LinkageGroupList, StrandStateMatrix-method), 18
- mergeFlankedLGs, LinkageGroupList, StrandStateMatrix-method, 18
- orderAllLinkageGroups (orderAllLinkageGroups, LinkageGroupList, StrandStateMatrix, StrandFreqMatrix, StrandReadMatrix-method), 19
- orderAllLinkageGroups, LinkageGroupList, StrandStateMatrix, StrandFreqMatrix, StrandReadMatrix-method, 19
- orderAllLinkageGroups, orderAllLinkageGroups-LinkageGroupList-StrandStateMatrix-StrandFreqMatrix-StrandReadMatrix-method (orderAllLinkageGroups, LinkageGroupList, StrandStateMatrix, StrandFreqMatrix, StrandReadMatrix-method), 19
- orderContigsGreedy, 20
- orderContigsTSP, 20
- OrientationFrame (OrientationFrame-class), 21
- OrientationFrame-class, 21
- plotContigOrder (plotContigOrder, ContigOrdering-method), 22
- plotContigOrder, ContigOrdering-method, 22
- plotLGDistances (plotLGDistances, LinkageGroupList, StrandStateMatrix-method), 22
- plotLGDistances, LinkageGroupList, LinkageGroupList-method, (plotLGDistances, LinkageGroupList, StrandStateMatrix-method), 22
- plotLGDistances, LinkageGroupList, StrandStateMatrix-method, thoroughBed, ANY, LibraryGroupList-method, 22
- plotWCdistribution (plotWCdistribution, StrandFreqMatrix-method), 23
- plotWCdistribution, StrandFreqMatrix, StrandFreqMatrix-method (plotWCdistribution, StrandFreqMatrix-method), 23
- plotWCdistribution, StrandFreqMatrix, StrandFreqMatrix-method, thoroughBed, StrandFreqMatrix-method, 23
- preprocessStrandTable (preprocessStrandTable, StrandFreqMatrix-method), 24
- preprocessStrandTable, StrandFreqMatrix, StrandFreqMatrix-method, (preprocessStrandTable, StrandFreqMatrix-method), 24
- preprocessStrandTable, StrandFreqMatrix-method, reorientAndMergeLGs (reorientAndMergeLGs, LinkageGroupList, StrandStateMatrix-method), 25
- reorientAndMergeLGs, LinkageGroupList, StrandStateMatrix-method, (reorientAndMergeLGs, LinkageGroupList, StrandStateMatrix-method), 25
- show, ContigOrdering-method, 26
- show, LibraryGroupList-method, 26
- show, StrandStateMatrix, StrandFreqMatrix, StrandReadMatrix-method, 27
- show, LinkageGroupList-method, 27
- show, OrientationFrame-method, 27
- show, StrandFreqMatrix, StrandFreqMatrix, StrandReadMatrix-method, 28
- show, StrandReadMatrix-method, 28
- show, StrandStateList-method, 29
- show, StrandStateMatrix, StrandFreqMatrix, StrandReadMatrix-method, 29
- StrandFreqMatrix (StrandFreqMatrix-class), 30
- StrandFreqMatrix-class, 30
- StrandReadMatrix (StrandReadMatrix-class), 30
- StrandReadMatrix-class, 30
- strandSeqFreqTable, 31
- StrandStateList (StrandStateList-class), 32
- StrandStateList-class, 32
- StrandStateMatrix (StrandStateMatrix-class), 32
- StrandStateMatrix-class, 32
- thoroughBed (thoroughBed, ANY, LibraryGroupList-method), 33
- thoroughBed, ANY, LibraryGroupList-method, 33
- thoroughBed, thoroughBed-LibraryGroupList-method (thoroughBed, ANY, LibraryGroupList-method), 34
- writeBed (writeBed, ANY, OrientationFrame, ContigOrdering-method), 34

writeBed,ANY,OrientationFrame,ContigOrdering-method,
34
writeBed-OrientationFrame-ContigOrdering-method
(writeBed,ANY,OrientationFrame,ContigOrdering-method),
34