

# Package ‘PtH2O2lipids’

June 18, 2024

**Title** P. tricornutum HPLC-ESI-MS Lipid Data from van Creveld et al. (2015)

**Version** 1.31.0

**Date** 2016-07-06

**Depends** R (>= 3.3), xcms, CAMERA, LOBSTAHS, methods, utils

**Suggests** gplots, RColorBrewer, cluster, vegan

**Description** Annotated HPLC-ESI-MS lipid data in positive ionization mode from an experiment in which cultures of the marine diatom *Phaeodactylum tricornutum* were treated with various concentrations of hydrogen peroxide (H<sub>2</sub>O<sub>2</sub>) to induce oxidative stress. The experiment is described in Graff van Creveld, et al., 2015, "Early perturbation in mitochondria redox homeostasis in response to environmental stress predicts cell fate in diatoms," *ISME Journal* 9:385-395. PtH2O2lipids consists of two objects: A CAMERA `xsAnnotate` object (`ptH2O2lipids$xsAnnotate`) and LOBSTAHS `LOBSet` object (`ptH2O2lipids$xsAnnotate$LOBSet`). The `LOBSet` includes putative compound assignments from the default LOBSTAHS database. Isomer annotation is recorded in three other `LOBSet` slots.

**License** MIT + file LICENSE

**URL** <http://dx.doi.org/10.1038/ismej.2014.136>,  
<https://github.com/vanmooylipidomics/PtH2O2lipids>,  
<http://www.whoi.edu/page.do?pid=133616&tid=282&cid=192529>

**BugReports** <https://github.com/vanmooylipidomics/PtH2O2lipids/issues/new>

**biocViews** ReproducibleResearch, CellCulture, MassSpectrometryData, *Phaeodactylum\_tricornutum\_data*

**NeedsCompilation** no

**Author** Shiri Graff van Creveld [aut], Shilo Rosenwasser [aut], Daniella Schatz [aut], Ilan Koren [aut], Assaf Vardi [aut], James Collins [cre]

**Maintainer** James Collins <james.r.collins@aya.yale.edu>

**git\_url** <https://git.bioconductor.org/packages/PtH2O2lipids>

**git\_branch** devel

**git\_last\_commit** 30faaa8

**git\_last\_commit\_date** 2024-04-30

**Repository** Bioconductor 3.20

**Date/Publication** 2024-06-18

## Contents

|              |          |
|--------------|----------|
| ptH2O2lipids | 2        |
| <b>Index</b> | <b>5</b> |

---

|              |                                                                             |
|--------------|-----------------------------------------------------------------------------|
| ptH2O2lipids | <i>P. tricornutum HPLC-ESI-MS Lipid Data from van Creveld et al. (2015)</i> |
|--------------|-----------------------------------------------------------------------------|

---

## Description

Positive ionization mode HPLC-ESI-MS lipid data from an experiment in which cultures of the marine diatom *Phaeodactylum tricornutum* were treated with various concentrations of hydrogen peroxide (H2O2) to induce oxidative stress. ptH2O2lipids\$LOBSet was generated from ptH2O2lipids\$xsAnnotate using the LOBSTAHS function [doLOBscreen](#).

## Usage

```
data(ptH2O2lipids)
```

## Format

A list object containing the lipid data in two forms:

ptH2O2lipids\$LOBSet A 1.2 MB object of formal class "[LOBSet](#)" containing screened peak data to which compound assignments and isomer identifications have been made. The structure of ptH2O2lipids\$LOBSet is:

```
Formal class 'LOBSet' [package "LOBSTAHS"] with 9 slots
 ..@ peakdata          : 'data.frame': 2056 obs. of 54 variables
 ..@ iso_C3r           : List of 2056
 ..@ iso_C3f           : List of 2056
 ..@ iso_C3c           : List of 2056
 ..@ LOBscreen_diagnostics: 'data.frame': 6 obs. of 4 variables:
 ..@ LOBisoID_diagnostics: 'data.frame': 3 obs. of 2 variables:
 ..@ LOBscreen_settings : List of 6
 .. ..$ database       : chr "default"
 .. ..$ remove.iso     : logi TRUE
 .. ..$ rt.restrict    : logi TRUE
```

```
.. ..$ rt.windows      : chr "default"  
.. ..$ exclude.oddFA: logi TRUE  
.. ..$ match.ppm      : num 2.5  
..@ polarity          : Factor w/ 1 level "positive": 1  
..@ sampnames         : chr [1:16] "0uM_24h_Orbi_0468" "0uM_24h_Orbi_0473" "0uM_4h_Orbi_0476" "0uM_4h_Orbi_0477" "0uM_4h_Orbi_0478" "0uM_4h_Orbi_0479" "0uM_4h_Orbi_0480" "0uM_4h_Orbi_0481" "0uM_4h_Orbi_0482" "0uM_4h_Orbi_0483" "0uM_4h_Orbi_0484" "0uM_4h_Orbi_0485" "0uM_4h_Orbi_0486" "0uM_4h_Orbi_0487" "0uM_4h_Orbi_0488"
```

ptH2O2lipids\$xsAnnotate An 80 MB object of formal class "`xsAnnotate`" containing 18,314 peakgroups in 5,080 pseudospectra. This is the object from which ptH2O2lipids\$LOBSet was created using `doLOBscreen`. It includes annotation of possible isotope peaks from `findIsotopes`. The `xcmsSet` from which the `xsAnnotate` object was created (64.5 MB) can be accessed at `ptH2O2lipids$xsAnnotate@xcmsSet`.

## Details

ptH2O2lipids\$LOBSet includes compound identifications assigned from the default LOBSTAHS positive mode database. ptH2O2lipids\$LOBSet also includes in the slots `iso_C3r`, `iso_C3f`, and `iso_C3c` the various possible isomers identified for each compound. Note that all other slots in the ptH2O2lipids object can be accessed using the accessor functions described for the "`LOBSet-class`" object class.

The dataset contains peaks from 16 samples that span three H2O2 treatments (0, 30 and 150  $\mu$ M) and three timepoints (+4, +8, and +24 hours) in duplicate. The dataset contains only one replicate sample for the 0 and 150  $\mu$ M treatments at +4h.

The mzXML files and Thermo .raw files from which these objects are derived can be accessed at <https://github.com/vanmooylipidomics/PtH2O2lipids/tree/master/mzXML> and <http://www.who.edu/page.do?pid=133616&tid=282&cid=192529>, respectively.

Users should note that the LOBSet in this package does not include any PUA (polyunsaturated aldehyde) identifications.

## Source

<http://www.nature.com/ismej/journal/v9/n2/full/ismej2014136a.html>

## References

Collins, J.R., B.R. Edwards, H.F. Fredricks, and B.A.S. Van Mooy. 2016. LOBSTAHS: An adduct-based lipidomics strategy for discovery and identification of oxidative stress biomarkers. *Analytical Chemistry*.

Graff van Creveld, et al., 2015, "Early perturbation in mitochondria redox homeostasis in response to environmental stress predicts cell fate in diatoms", *ISME Journal* 9:385-395

## See Also

[LOBSet-class](#), [LOBSet](#), [doLOBscreen](#), [getLOBpeaklist](#), [xcmsSet](#), [xsAnnotate](#)

**Examples**

```
## generate the object in ptH2O2lipids$LOBSet using ptH2O2lipids$xsAnnotate as
## input
library(PtH2O2lipids)

## yields output identical to ptH2O2lipids$LOBSet
myPtH2O2LOBSet = doLOBscreen(ptH2O2lipids$xsAnnotate, polarity = "positive",
database = NULL, remove.iso = TRUE, rt.restrict = TRUE, rt.windows = NULL,
exclude.oddFA = TRUE, match.ppm = 2.5)

## access xsAnnotate object
ptH2O2lipids$xsAnnotate

## access xcmsSet
ptH2O2lipids$xsAnnotate@xcmsSet
```

# Index

## \* datasets

ptH202lipids, [2](#)

doLOBscreen, [2](#), [3](#)

findIsotopes, [3](#)

getLOBpeaklist, [3](#)

LOBSet, [2](#), [3](#)

PtH202lipids (ptH202lipids), [2](#)

ptH202lipids, [2](#)

xcmsSet, [3](#)

xsAnnotate, [3](#)