

Package ‘alevinQC’

November 8, 2024

Type Package

Title Generate QC Reports For Alevin Output

Version 1.22.0

Date 2024-04-07

Description Generate QC reports summarizing the output from an alevin, alevin-fry, or simpleaf run.
Reports can be generated as html or pdf files, or as shiny applications.

Encoding UTF-8

SystemRequirements C++11

Depends R (>= 4.0)

Imports rmarkdown (>= 2.5), tools, methods, ggplot2 (>= 3.4.0), GGally, dplyr, rjson, shiny, shinydashboard, DT, stats, utils, tximport (>= 1.17.4), cowplot, rlang, Rcpp

RoxygenNote 7.3.1

Suggests knitr, BiocStyle, testthat (>= 3.0.0), BiocManager

VignetteBuilder knitr

biocViews QualityControl, SingleCell

URL <https://github.com/csoneson/alevinQC>

BugReports <https://github.com/csoneson/alevinQC/issues>

License MIT + file LICENSE

Config/testthat/edition 3

LinkingTo Rcpp

git_url <https://git.bioconductor.org/packages/alevinQC>

git_branch RELEASE_3_20

git_last_commit 92e4f1e

git_last_commit_date 2024-10-29

Repository Bioconductor 3.20

Date/Publication 2024-11-08

Author Charlotte Soneson [aut, cre] (<<https://orcid.org/0000-0003-3833-2169>>),
Avi Srivastava [aut],
Rob Patro [aut],
Dongze He [aut]

Maintainer Charlotte Soneson <charlottesoneson@gmail.com>

Contents

alevinQC-package	2
checkAlevinFryInputFiles	3
checkAlevinInputFiles	3
plotAlevinBarcodeCollapse	4
plotAlevinHistogram	5
plotAlevinKneeNbrGenes	6
plotAlevinKneeRaw	7
plotAlevinQuant	7
plotAlevinQuantPairs	8
qcReport	9
qcShiny	12
readAlevinFryQC	13
readAlevinQC	14
Index	15

alevinQC-package	<i>alevinQC</i>
------------------	-----------------

Description

alevinQC

Author(s)

Maintainer: Charlotte Soneson <charlottesoneson@gmail.com> ([ORCID](#))

Authors:

- Avi Srivastava
- Rob Patro
- Dongze He

See Also

Useful links:

- <https://github.com/csoneson/alevinQC>
- Report bugs at <https://github.com/csoneson/alevinQC/issues>

`checkAlevinFryInputFiles`*Check that all required input files are available for alevin-fry*

Description

Check that all required input files are available for alevin-fry

Usage

```
checkAlevinFryInputFiles(mapDir, permitDir, quantDir)
```

Arguments

<code>mapDir</code>	Path to the directory containing the map.rad file
<code>permitDir</code>	Path to the output directory of the alevin-fry generate-permit-list command.
<code>quantDir</code>	Path to the output of the alevin-fry quant command.

Value

Returns nothing, raises an error if any of the required files are missing.

Author(s)

Charlotte Soneson

Examples

```
checkAlevinFryInputFiles(  
  mapDir = system.file("extdata/alevinfry_example_v0.5.0/map",  
    package = "alevinQC"),  
  permitDir = system.file("extdata/alevinfry_example_v0.5.0/permit",  
    package = "alevinQC"),  
  quantDir = system.file("extdata/alevinfry_example_v0.5.0/quant",  
    package = "alevinQC"))
```

`checkAlevinInputFiles` *Check that all required input files are available*

Description

Check that all required input files are available

Usage

```
checkAlevinInputFiles(baseDir)
```

Arguments

`baseDir` Path to the output directory from the alevin run (should be the directory containing the alevin directory).

Value

Returns nothing, raises an error if any of the required files are missing.

Author(s)

Charlotte Sonesson

Examples

```
checkAlevinInputFiles(system.file("extdata/alevin_example_v0.14",
                                  package = "alevinQC"))
```

plotAlevinBarcodeCollapse

Summary plot of cell barcode collapsing

Description

Plot the original frequency of each cell barcode in the original whitelist against the frequency after collapsing similar cell barcodes.

Usage

```
plotAlevinBarcodeCollapse(
  cbTable,
  firstSelColName = "inFirstWhiteList",
  countCol = "collapsedFreq"
)
```

Arguments

`cbTable` `data.frame` (such as the `cbTable` returned by `readAlevinQC` or `readAlevinFryQC`) with barcode frequencies before and after collapsing.

`firstSelColName` Character scalar indicating the name of the logical column in `cbTable` that corresponds to the original selection of barcodes for quantification.

`countCol` Character scalar indicating the name of the column in `cbTable` that corresponds to the collapsed barcode frequencies.

Value

A `ggplot` object

Author(s)

Charlotte Sonesson

Examples

```
alevin <- readAlevinQC(system.file("extdata/alevin_example_v0.14",
                                  package = "alevinQC"))
plotAlevinBarcodeCollapse(alevin$cbTable)
```

plotAlevinHistogram *Histogram of selected summary statistic*

Description

Histogram of selected summary statistic

Usage

```
plotAlevinHistogram(
  cbTable,
  plotVar = "dedupRate",
  axisLabel = plotVar,
  colName = "inFinalWhiteList",
  cbName = "final whitelist",
  firstSelColName = "inFirstWhiteList"
)
```

Arguments

cbTable	data.frame (such as the cbTable returned by readAlevinQC or readAlevinFryQC) containing the desired summary statistic in a column.
plotVar	Character scalar giving the name of a numeric column of cbTable to plot.
axisLabel	Character scalar giving the label of the selected statistic (will be displayed as the axis label in the plot).
colName	Character scalar giving the name of a logical column of cbTable to use for filling the bars in the histogram.
cbName	Character scalar giving the name of the set of barcodes defined by colName, used for labelling the plot legend.
firstSelColName	Character scalar indicating the name of the logical column in cbTable that corresponds to the original selection of barcodes for quantification.

Value

A ggplot object

Author(s)

Charlotte Soneson

Examples

```
alevin <- readAlevinQC(system.file("extdata/alevin_example_v0.14",
                                package = "alevinQC"))
plotAlevinHistogram(alevin$cbTable, plotVar = "dedupRate",
                    axisLabel = "Deduplication rate",
                    colName = "inFinalWhiteList",
                    cbName = "final whitelist")
```

plotAlevinKneeNbrGenes

Knee plot of the number of detected genes per cell

Description

Plot the number of detected genes per cell in decreasing order. Only cells contained in the original whitelist are considered.

Usage

```
plotAlevinKneeNbrGenes(cbTable, firstSelColName = "inFirstWhiteList")
```

Arguments

cbTable data.frame (such as the cbTable returned by readAlevinQC or readAlevinFryQC) with the number of detected genes per cell.

firstSelColName Character scalar indicating the name of the logical column in cbTable that corresponds to the original selection of barcodes for quantification.

Value

A ggplot object

Author(s)

Charlotte Sonesson

Examples

```
alevin <- readAlevinQC(system.file("extdata/alevin_example_v0.14",
                                package = "alevinQC"))
plotAlevinKneeNbrGenes(alevin$cbTable)
```

plotAlevinKneeRaw	<i>Knee plot of raw cell barcode frequencies</i>
-------------------	--

Description

Plot the raw cell barcode frequencies in decreasing order, and indicate a predetermined breakpoint (indicating barcodes included in the original whitelist) using color as well as a label.

Usage

```
plotAlevinKneeRaw(cbTable, firstSelColName = "inFirstWhiteList")
```

Arguments

cbTable	data.frame with raw barcode frequencies (such as the cbTable returned by readAlevinQC or readAlevinFryQC).
firstSelColName	Character scalar indicating the name of the logical column in cbTable that corresponds to the original selection of barcodes for quantification.

Value

A ggplot object

Author(s)

Charlotte Soneson

Examples

```
alevin <- readAlevinQC(system.file("extdata/alevin_example_v0.14",  
                                package = "alevinQC"))  
plotAlevinKneeRaw(alevin$cbTable)
```

plotAlevinQuant	<i>Panel of plots with quantification summary statistics</i>
-----------------	--

Description

Panel of plots with quantification summary statistics

Usage

```
plotAlevinQuant(  
  cbTable,  
  colName = "inFinalWhiteList",  
  cbName = "final whitelist",  
  firstSelColName = "inFirstWhiteList"  
)
```

Arguments

cbTable	data.frame (such as the cbTable returned by readAlevinQC or readAlevinFryQC) with collapsed barcode frequencies, the total UMI count and the number of detected genes for each cell.
colName	Character scalar giving the name of a logical column of cbTable to use for coloring the points.
cbName	Character scalar giving the name of the set of barcodes defined by colName, used for labelling the plot legend.
firstSelColName	Character scalar indicating the name of the logical column in cbTable that indicates the original selection of barcodes for quantification.

Value

A ggplot object

Author(s)

Charlotte Soneson

Examples

```
alevin <- readAlevinQC(system.file("extdata/alevin_example_v0.14",
                                   package = "alevinQC"))
plotAlevinQuant(alevin$cbTable, colName = "inFinalWhiteList",
                cbName = "final whitelist")
```

plotAlevinQuantPairs *Pairs plot with quantification summary statistics*

Description

Pairs plot with quantification summary statistics

Usage

```
plotAlevinQuantPairs(
  cbTable,
  colName = "inFinalWhiteList",
  firstSelColName = "inFirstWhiteList"
)
```

Arguments

cbTable	data.frame (such as the cbTable returned by readAlevinQC or readAlevinFryQC) with collapsed barcode frequencies, the total UMI count and the number of detected genes for each cell.
colName	Character scalar giving the name of a logical column of cbTable to use for coloring the points.
firstSelColName	Character scalar indicating the name of the logical column in cbTable that corresponds to the original selection of barcodes for quantification.

Value

A ggmatrix object

Author(s)

Charlotte Soneson

Examples

```
alevin <- readAlevinQC(system.file("extdata/alevin_example_v0.14",  
                                package = "alevinQC"))  
plotAlevinQuantPairs(alevin$cbTable, colName = "inFinalWhiteList")
```

qcReport

Generate alevin/alevin-fry summary report

Description

Generate a report summarizing the main aspects of an alevin/alevin-fry quantification run. The report generation assumes that alevin/alevin-fry has been run with the `–dumpFeatures` flag to generate the necessary output files.

Usage

```
alevinQCReport(  
  baseDir,  
  sampleId,  
  outputFile,  
  outputDir = "./",  
  outputFormat = NULL,  
  showCode = FALSE,  
  forceOverwrite = FALSE,  
  knitrProgress = FALSE,  
  quiet = FALSE,  
  ignorePandoc = FALSE,  
  customCBLIST = list(),  
  ...  
)  
  
simpleafQCReport(  
  simpleafQuantDir,  
  sampleId,  
  outputFile,  
  outputDir = "./",  
  outputFormat = NULL,  
  showCode = FALSE,  
  forceOverwrite = FALSE,  
  knitrProgress = FALSE,  
  quiet = FALSE,  
  ignorePandoc = FALSE,
```

```

    customCBList = list(),
    ...
)

alevinFryQCReport(
  mapDir,
  permitDir,
  quantDir,
  sampleId,
  outputFile,
  outputDir = "./",
  outputFormat = NULL,
  showCode = FALSE,
  forceOverwrite = FALSE,
  knitrProgress = FALSE,
  quiet = FALSE,
  ignorePandoc = FALSE,
  customCBList = list(),
  ...
)

```

Arguments

baseDir	(Only used for alevin output) Path to the output directory from the alevin run (should be the directory containing the alevin directory).
sampleId	Sample ID, will be used to set the title for the report.
outputFile	File name of the output report. The file name extension must be either .html or .pdf, and consistent with the value of outputFormat.
outputDir	Path to the output directory where the report will be generated.
outputFormat	The format of the output report. Either "html_document", "pdf_document", "BiocStyle::html_document" or "BiocStyle::pdf_document". The file name extension of outputFile must be consistent with this choice.
showCode	Logical, whether to display the R code in the report.
forceOverwrite	Logical, whether to force overwrite an existing report with the same name in the output directory.
knitrProgress	Logical, whether to display the progress of knitr when generating the report.
quiet	Logical, whether to show progress messages.
ignorePandoc	Logical, determines what to do if pandoc or pandoc-citeproc is missing (if Sys.which("pandoc") or Sys.which("pandoc-citeproc") returns ""). If ignorePandoc is TRUE, only a warning is given. The figures will be generated, but not the final report. If ignorePandoc is FALSE (default), the execution stops immediately.
customCBList	Named list with custom set(s) of barcodes to provide summary statistics/plots for, in addition to the whitelists generated by alevin.
...	Other arguments that will be passed to rmarkdown::render.
simpleafQuantDir	(Only used for simpleaf output) Path to the output directory from the simpleaf run (should be the directory containing the af_map and af_quant directories).

mapDir	(Only used for alevin-fry output) Path to the output directory from the salmon alevin run (should be the directory containing the map.rad file).
permitDir	(Only used for alevin-fry output) Path to the output directory from the permit list generation step (should be the directory containing the all_freq.tsv file).
quantDir	(Only used for alevin-fry output) Path to the output directory from the alevin-fry quantification step (should be the directory containing the alevin directory).

Details

When the function is called, a .Rmd template file will be copied into the output directory, and `rmarkdown::render` will be called to generate the final report. If there is already a .Rmd file with the same name in the output directory, the function will raise an error and stop, to avoid overwriting the existing file. The reason for this behaviour is that the copied template in the output directory will be deleted once the report is generated.

Value

Generates a summary report in the `outputDir` directory, and returns (invisibly) the name of the generated report.

Author(s)

Charlotte Soneson

Examples

```
alevinQCReport(
  baseDir = system.file("extdata/alevin_example_v0.14",
                        package = "alevinQC"),
  sampleId = "example", outputFile = "alevinReport.html",
  outputDir = tempdir(), forceOverwrite = TRUE)

alevinFryQCReport(
  mapDir = system.file("extdata/alevinfry_example_v0.5.0/map",
                       package = "alevinQC"),
  permitDir = system.file("extdata/alevinfry_example_v0.5.0/permit",
                           package = "alevinQC"),
  quantDir = system.file("extdata/alevinfry_example_v0.5.0/quant",
                           package = "alevinQC"),
  sampleId = "example", outputFile = "alevinFryReport.html",
  outputDir = tempdir(), forceOverwrite = TRUE)

simpleafQCReport(
  simpleafQuantDir = system.file("extdata/alevinfry_example_piscem_v0.6.0",
                                 package = "alevinQC"),
  sampleId = "example", outputFile = "simpleafReport.html",
  outputDir = tempdir(), forceOverwrite = TRUE)
```

qcShiny

*Generate alevin/alevin-fry summary shiny app***Description**

Generate a shiny app summarizing the main aspects of an alevin/alevin-fry quantification run. The app generation assumes that alevin has been run with the `-dumpFeatures` flag to generate the necessary output files.

Usage

```
alevinQCShiny(baseDir, sampleId, customCBLIST = list())
```

```
alevinFryQCShiny(mapDir, permitDir, quantDir, sampleId)
```

```
simpleafQCShiny(simpleafQuantDir, sampleId)
```

Arguments

<code>baseDir</code>	(Only used for alevin output) Path to the output directory from the alevin run (should be the directory containing the alevin directory).
<code>sampleId</code>	Sample ID, will be used set the title for the app.
<code>customCBLIST</code>	Named list with custom set(s) of barcodes to provide summary statistics/plots for, in addition to the whitelists generated by alevin.
<code>mapDir</code>	(Only used for alevin-fry output) Path to the output directory from the salmon alevin run (should be the directory containing the <code>map.rad</code> file).
<code>permitDir</code>	(Only used for alevin-fry output) Path to the output directory from the permit list generation step (should be the directory containing the <code>all_freq.tsv</code> file).
<code>quantDir</code>	(Only used for alevin-fry output) Path to the output directory from the alevin-fry quantification step (should be the directory containing the alevin directory).
<code>simpleafQuantDir</code>	(Only used for simpleaf output) Path to the output directory from the simpleaf run (should be the directory containing the <code>af_map</code> and <code>af_quant</code> directories).

Value

A shiny app.

Author(s)

Charlotte Sonesson

Examples

```
app <- alevinQCShiny(
  baseDir = system.file("extdata/alevin_example_v0.14",
    package = "alevinQC"),
  sampleId = "example")
if (interactive()) {
  shiny::runApp(app)
```

```

}

app <- alevinFryQCShiny(
  mapDir = system.file("extdata/alevinfry_example_v0.5.0/map",
    package = "alevinQC"),
  permitDir = system.file("extdata/alevinfry_example_v0.5.0/permit",
    package = "alevinQC"),
  quantDir = system.file("extdata/alevinfry_example_v0.5.0/quant",
    package = "alevinQC"),
  sampleId = "example")
if (interactive()) {
  shiny::runApp(app)
}

app <- simpleafQCShiny(
  simpleafQuantDir = system.file("extdata/alevinfry_example_piscem_v0.6.0",
    package = "alevinQC"),
  sampleId = "example")
if (interactive()) {
  shiny::runApp(app)
}

```

readAlevinFryQC

Read alevin-fry data required to generate summary report

Description

Read all alevin-fry output files required to generate the summary report or shiny app.

Usage

```
readAlevinFryQC(mapDir, permitDir, quantDir)
```

Arguments

mapDir	Path to the output directory from the salmon alevin run (should be the directory containing the alevin folder).
permitDir	Path to the output directory from the generate-permit-list and collate runs.
quantDir	Path to the output directory from the alevin-fry quant run (should be the directory containing the alevin folder).

Value

A list collecting all necessary information for generating the summary report/shiny app.

Author(s)

Charlotte Soneson

Examples

```
alevinfry <- readAlevinFryQC(  
  mapDir = system.file("extdata/alevinfry_example_v0.5.0/map",  
    package = "alevinQC"),  
  permitDir = system.file("extdata/alevinfry_example_v0.5.0/permit",  
    package = "alevinQC"),  
  quantDir = system.file("extdata/alevinfry_example_v0.5.0/quant",  
    package = "alevinQC"))
```

readAlevinQC	<i>Read alevin data required to generate summary report</i>
--------------	---

Description

Read all alevin output files required to generate the summary report or shiny app.

Usage

```
readAlevinQC(baseDir, customCBLlist = list())
```

Arguments

baseDir	Path to the output directory from the alevin run (should be the directory containing the alevin directory).
customCBLlist	Named list with custom set(s) of barcodes to provide summary statistics/plots for, in addition to the whitelists generated by alevin.

Value

A list collecting all necessary information for generating the summary report/shiny app.

Author(s)

Charlotte Soneson

Examples

```
alevin <- readAlevinQC(system.file("extdata/alevin_example_v0.14",  
  package = "alevinQC"))
```

Index

* internal

alevinQC-package, [2](#)

alevinFryQCReport (qcReport), [9](#)

alevinFryQCShiny (qcShiny), [12](#)

alevinQC (alevinQC-package), [2](#)

alevinQC-package, [2](#)

alevinQCReport (qcReport), [9](#)

alevinQCShiny (qcShiny), [12](#)

checkAlevinFryInputFiles, [3](#)

checkAlevinInputFiles, [3](#)

plotAlevinBarcodeCollapse, [4](#)

plotAlevinHistogram, [5](#)

plotAlevinKneeNbrGenes, [6](#)

plotAlevinKneeRaw, [7](#)

plotAlevinQuant, [7](#)

plotAlevinQuantPairs, [8](#)

qcReport, [9](#)

qcShiny, [12](#)

readAlevinFryQC, [13](#)

readAlevinQC, [14](#)

simpleafQCReport (qcReport), [9](#)

simpleafQCShiny (qcShiny), [12](#)